




DC Inverter
Cooling only

A⁺⁺

Airwell

FDLK

Low-temperature floor ceiling



RCW25
included

+ PRODUCT

- RCW25 remote control included
- Minimum temperature setpoint of 12 °C
- Robust and tough: metal structure

FEATURES

TECHNOLOGY



ELECTRONIC
EXPANSION VALVE

AIR QUALITY



FRESH AIR

USER FUNCTIONS



I FEEL



NIGHT MODE



24 H
PROGRAMMABLE
TIMER



RESTART
(MEMORY)



REMOTE CONTROL
LOCK

INSTALLER FUNCTIONS



ERROR PART NUMBER
VIA INDOOR UNIT



AUTO-DIAGNOSTIC



LEFT/RIGHT
CONDENSATE
CONNECTION



ALARM OUTPUT



DRY CONTACT
ON/OFF



TEST MODE
TECHNICIAN TEST
MODE

+ «SUSTAINABLE DEVELOPMENT»

- > High energy class A++.

+ «USER»

- > Dedicated solution for low-temperature rooms (wine cellars, preparation rooms, household waste areas, etc.).
- > The indoor unit is more compact and lighter than the previous version, allowing it to be easily built-in even in small spaces.
- > With an optimized air flow rate, the temperature set point can be achieved more quickly.

+ «INSTALLER»

- > Ease of installation.

+ «TECHNOLOGY»

- > Oversized exchangers (no frosting and LP protection).

OPTIONS

ACCESSORY

PART NUMBER

PICTURE

FUNCTION

Condensate pump
Mini Flowwatch MF2

7ACTL0517



- Condensate evacuation from indoor units.

Dedicated for any low-temperature process rooms

- > Minimum temperature setpoint 12 °C



TECHNICAL DATA

FDLK

INDOOR UNIT		FDLK-050N-09M25	FDLK-070N-09M25
Part number		7SP012315	7SP012316
Phase		Single-phase	Single-phase

COOLING

Rated power (min./max.)	kW	5.30 (2.00-5.60)	7.00 (3.50-8.00)
Pdesignc	kW	5.30	7.10
Rated power input	kW	1.495	2.093
SEER/Energy label		6.1/A++	6.1/A++
Operating limits	°C	-15°/50° Dry bulb	

INDOOR UNIT

Sound pressure level at 1 m (LS/MS/HS)	dB(A)	36/42/47	36/42/47
Sound level	dB(A)	52	52
Airflow (LS/MS/HS)	m³/h	900/1050/1200	900/1050/1200
Dehumidification	l/h	1.80	2.40
Unit dimensions (WxHxD)	mm	1050x675x235	1050x675x235
Package dimensions (WxHxD)	mm	1130x765x330	1130x765x330
Net weight/Gross weight	kg	26.5/31	26.5/31

OUTDOOR UNIT		YDAK-050R-09M25	YDAK-070R-09M25
Part number		7SP063195	7SP063196
Sound pressure level at 1 m	dB(A)	52	54
Sound level	dB(A)	66	68
Airflow	m³/h	1950	3200
Compressor type		Rotary DCI	Twin Rotary DCI
Unit dimensions (WxHxD)	mm	880x555x345	935x702x382
Package dimensions (WxHxD)	mm	920x600x380	975x770x435
Net weight/Gross weight	kg	32.5/35	48.7/52.6

POWER SUPPLY

Phase/Voltage/Frequency		1P/230V/50Hz	1P/230V/50Hz
Power supply side		Outdoor	Outdoor
Power cable section	mm²	3x2.5	3x2.5
Max. current (D curve)	A	20	20
Electrical connections	mm²	4x1.5	4x1.5

PIPE LINE

Suction pipe diameter	inches	1/2"	5/8"
Liquid pipe diameter	inches	1/4"	3/8"
Max. length	m	15	20
Max. height	m	8	10
Refrigerant/GWP		R32/675	R32/675
Charge	kg	1.20	1.45
Additional charge	g/m	12	24

MATCHING

INDOOR UNIT	COMPATIBLE WITH OUTDOOR UNIT
FLOOR CEILING	MONOSPLIT
 FDLK	 YDAK

GRUPE AIRWELL

10, RUE DU FORT DE SAINT CYR - 78180 MONTIGNY LE BRETONNEUX, FRANCE

TEL.: +33 (0)1 76 21 82 00 - www.airwell.com