



Fixed speed
Cooling only

A⁺

Airwell

MFH Portable



RC08C
included

+ PRODUCT

- RC08C remote control included
- Monoblock solution
- No fluid handling

FEATURES

TECHNOLOGY



ANTIBACTERIAL
FILTER



AUTO
CLEAN/DRY

USER FUNCTIONS



I FEEL



NIGHT MODE



24 H
PROGRAMMABLE
TIMER



RESTART
(MEMORY)



REMOTE CONTROL
LOCK

INSTALLER FUNCTIONS



AUTO-DIAGNOSTIC

+ «SUSTAINABLE DEVELOPMENT»

- > Environmentally friendly R290 refrigerant.

+ «USER»

- > Easy to move thanks to its castors and handles.
- > Easy reading thanks to its digital display on the control panel.
- > Remotely controllable with the RC unit.
- > High comfort thanks to its cooling capacity.

+ «TECHNOLOGY»

- > Caulking kit included.
- > Condensate evacuation by evaporation.

TECHNICAL DATA

INDOOR UNIT		AW-MFH010-C41	AW-MFH012-C41
Part number		7MB021060	7MB021061
Phase		Single-phase	Single-phase
COOLING			
Rated power	kW	2.93	3.52
Rated power input	kW	0.945	1.357
Courant	A	4.50	5.90
EER/Energy label		3.10/A+	2.60/A
Operating limits	°C	17°/35° Dry bulb	
INDOOR UNIT			
Type		Monoblock	Monoblock
Sound pressure level at 1 m (LS/MS/HS)	dB(A)	50/51/52	50/51/52
Sound level	dB(A)	62	63
Airflow (LS/MS/HS)	m ³ /h	355/370/420	355/370/420
Diameter flexible emission duct	mm	150	
Length range of heat emission duct	m	0.50 - 1.50	
Dehumidification	l/h	1.60	1.80
Unit dimensions (WxHxD)	mm	467x765x397	467x765x397
Package dimensions (WxHxD)	mm	515x890x440	515x890x440
Net weight/Gross weight	kg	31.8/35.7	33/36.5
POWER SUPPLY			
Phase/Voltage/Frequency		1P/230V/50Hz	1P/230V/50Hz
PIPE LINE			
Refrigerant/GWP		R290/20	R290/20
Charge	kg	0.21	0.22

*Min. pack 8 pcs.