


75^{years}
AIRWELL

1947 - 2022

WORLD LEADERS

Airwell

2022 • 2023 EUROPE CATALOGUE
VRF RANGE • Variable Refrigerant Flow solutions

 FRENCH BRAND

Airwell

YOUR FRENCH
EXPERT *for the past 75 years*



Airwell CELEBRATING ITS
75th ANNIVERSARY
and becomes a french group again

GROUPE AIRWELL

Promising times in store for a historic brand created in 1947,
and which has retained its DNA ever since:

RELIABILITY • SERVICE • PARTNERSHIP • INNOVATION

OUR PRODUCTS

- Air/water range
- Air/air range
- Water-cooled range
- Tertiary and industrial range
- Solar range

OUR CERTIFICATIONS

- *Airwell* participates in the ECP programme for ACI. Check ongoing validity of certificate: www.eurovent-certification.com



- Company compliant with standard **ISO 9001**



IN FIGURES

- **1st european manufacturer** for air conditioning and heat pumps
- **More than 75 years** of experience
- Present in **80 countries**
- **more than 6500 references** in stock



AFTER-SALES AND QUALITY SERVICE



+33 (0)1 76 21 82 95

Monday to Friday
9 am-12:30 pm / 2 pm-5 pm

ORDER SPARE PARTS

sp@airwell.com

TECHNICAL SUPPORT

sav@airwell.com

We want our customers to be satisfied with our services, which is why our teams constantly monitor our spare parts stock.

Our interactive voice server (IVR) has been redesigned in order to provide more efficient and effective customer service. Our responsiveness and professionalism aim for a benchmark level of service.

ABOUT US

A French brand regarded as the professional benchmark

A French expert and developer of HVAC solutions for the past 75 years, Airwell's mission has always been to create and cultivate well-being.

A vision of the future. Airwell was created in 1947 out of the crazy idea of bringing from United States innovative solutions that did not exist yet in Europe: air conditioning.

Today, **innovation is more crucial to Airwell than ever**, given our status as leaders in the creation of HVAC solutions. We apply a profoundly human approach to innovation, listening to our consumers, and like the family spirit that defines Airwell, is based on the common good, with due regard to everyone's expectations.

Optimize our energetic consumption, promoting solar energy to preserve our natural resources, reinventing consumer practices to limit our environmental footprint, cultivating home comfort... At Airwell, we are committed to these issues, for the well-being of all and for the environment.

"What was just an ambition for us has become our mission."

OUR COMMITMENTS

Service is our priority

- Design of unique solutions
- Our DNA: partnership
- Help in making your projects a success
- Local and remote technical support

French Quality and Expertise

- A historic French brand
- Innovative and competitive solutions
- Wide range of products to adapt to every need

OUR VALUES AND CORPORATE CULTURE

INNOVATION • SERENITY • COMFORT LISTENING • COMMITMENT

"Just feel well" sums up our corporate culture, based on lasting relationships for the common good, in which everyone is respected.

An extended family including employees, distributors, installers, maintenance technicians, partners and consumers.

"A big family where everyone brings value to the business."



SMART HOME

Solutions

MODEL

p.6 AIRCONNECT SMART APP



p.8 AIRCONNECT PRO APP





Control
**YOUR VRF SYSTEM
FROM ANYWHERE**

The FlowLogic VRF system can be remotely controlled by the intelligent WiFi module and controlled by the AirConnect Smart application.

1

Control your Airwell VRF air conditioning system wherever you are, up to 4 VRF systems and 64 indoor units.

2

Pair all your indoor units at once thanks to Airwell WiFi Bus Control technology.

3

Multi-site management: quick and easy to use for managing several sites equipped with Airwell VRF from your smartphone.

4

Create your own regulation for greater comfort, maximum efficiency and energy savings with the automation and scenario platform.

5


Add a multitude of connected objects.

To download the application, it's simple: just scan the QR code.






SMART WIFI MODULE:
 ▶ Part number: 7ACEL1869




- ▶ **Module dimension:** 86x86x12 mm
- ▶ **Compatible models:** VVFA, VVTA, VVEA

INSTALLATION METHOD

▶ Thanks to Airwell WiFi Bus Control, a single pairing to connect all your indoor units.



▶ The Airwell VRF can be associated with both the central controller (RWV06, RWV09) and the AirConnect Smart WiFi module.



Smart

AIRCONNECT PRO



Global solution

THE CONTROL AND PREVENTIVE MAINTENANCE OF VRF INSTALLATIONS

accessible on smartphone, tablet* or computer



www.airconnectpro.com

* For the Control App.



Télécharger dans
l'App Store



DISPONIBLE SUR
Google play



Simple data collection with the AirConnect Pro cloud box

Up to 2 VRF systems and 128 indoor units managed by one AirConnect Pro box.

OPTIMAL THERMAL COMFORT

Entrust your thermal comfort to Air-ConnectPro, in order to free you from technical constraints and operational hazards.

HISTORY MANAGEMENT

Access the complete operating history (fluidic and electrical) of each indoor and outdoor unit from the day of commissioning. Make comparisons between periods or between sites.

VISUALIZATION OF YOUR VRF FLEET

View the settings of all your VRF spread across a city, region, country or around the world.

ALERT MANAGEMENT

Be alerted to the slightest drift! Alerts, anomalies can be sent directly to your technicians depending on the level of technicality or their geographical proximity.

PREVENTIVE MAINTENANCE

Easily create your anticipation rules to prevent any problems or untimely shutdown of your systems.

CREATION OF TECHNICAL DIAGNOSTICS

Carry out your technical diagnostics in no time and offer a technical service of unparalleled quality and speed while optimizing the work of on-site technicians.



AIRCONNECT PRO IS A COMPLETE SOLUTION THAT OFFERS 3 LEVELS OF SERVICE:

- ▶ **CONTROL APP:** control of indoor units
- ▶ **SERVICE APP:** diagnostic and preventive maintenance
- ▶ **MANAGEMENT APP:** site management, energy metering and optimization

CONTROL APP (CONTROL OF INDOOR UNITS)	<ul style="list-style-type: none"> • Unique solution for remote control of indoor units • Management of modes, setpoint temperatures, fan speed • "Weekly schedule" programming without rule limitation • Creation of control zones allowing energy savings
SERVICE APP (DIAGNOSIS AND PREVENTIVE MAINTENANCE)	<ul style="list-style-type: none"> • The ONLY preventive remote maintenance solution on the market: Prevent a breakdown before it happens! • Remote visualization of all the parameters of the installations • VRF and diagnosis in one click • Recording of all the data allowing a complete history of history of operation • Management and follow-up of alerts to designated technicians
MANAGEMENT APP (METERING AND ENERGY OPTIMIZATION) (IN DÉVELOPPENT)	<ul style="list-style-type: none"> • The most reliable and accurate energy metering solution on the market. Thanks to the Modbus MID meter, it allows the distribution of consumption per indoor unit according to its operating parameters. • Division of the global consumption by indoor unit or by zone • Energy audit of the installation allowing energy savings • Comparison of consumption by system or by site in order to optimize the operation of the machines and reduce energy costs

PRODUCT & SERVICE REFERENCES

	1 ST YEAR PACK	FROM THE 2 ND YEAR
	Cloud Box AirConnect Pro License of CONTROL APP without limitation of time. 1 year SERVICE APP license for the maintenance solution.	Tacit renewal of the license of SERVICE APP. In the event of termination of the SERVICE APP, the CONTROL APP application remains usable for life.
AIRCONNECT PRO CLOUD BOX	SO3199999	
LIFETIME CONTROL APP LICENSE PER CLOUD BOX	SO3299999	
SERVICE APP LICENSE PER SYSTEM & PER YEAR	SO30120xx	xx = system capacity





COMMERCIAL & INDUSTRIAL

Ranges

THE VRF AIRWELL OFFER

A manufacturing concept built on experience and an international presence. Product designed to meet European energy efficiency prerogatives while being resistant to harsh climatic environments.

Airwell VRFs are 100% Inverter

The new VRF Inverter range exclusively uses the best Japanese compressor brands and focusing on 3 technologies: the **Scroll EVI, the Scroll and the Twin Rotary**, thus offering a perfect ratio between reliability and energy efficiency.

All the refrigeration units of the Airwell VRFs have been strictly selected to guarantee flawless reliability and increased service life.

Among the most notable refrigeration components are the Japanese compressors and the oversized «anti-liquid shock» bottle protecting it. An oil separator per compressor allowing a direct return of more than 95% of the oil expelled during discharge and a sub-cooler with an adjustable target during development.

In addition, each Airwell VRF is protected by a series of sensors allowing the correct operation and energy efficiency of the installation to be guaranteed at all times.

Airwell communication bus

Thanks to the disconnection of the indoor units, it allows the system to remain in operation, offering greater comfort to end customers during service and maintenance operations.

Silent mode

Silent mode allows installation in restricted urban areas.

Anti-corrosion treatment

Standard anti-corrosion treatment offering resistance to salt spray for more than 500 hours and reinforced anti-corrosion treatment on request to meet the most demanding constraints.


**OUTDOOR UNIT
MODELS**
REFRIGERANT
TYPECAPACITY
(HP)COOLING
CAPACITY
(kW)HEATING
CAPACITY
(kW)

p.13

VVFA - 2-PIPES - FRONT DISCHARGE


VVFA-125R

4

12.10

14.20

VVFA-150R

6

15.50

18.00

VVFA-220R

R410A

8

22.60

22.60

VVFA-280R

10

28.00

30.50

VVFA-335R

12

31.50

31.50

p.16

VVTA - 2 PIPES - TOP DISCHARGE


VVTA-250R

8

25.20

25.20

VVTA-280R

10

28.00

28.00

VVTA-335R

12

33.50

33.50

VVTA-400R

14

40.00

40.00

VVTA-450R

R410A

16

45.00

45.00

VVTA-504R

18

50.40

50.40

VVTA-560R

20

56.00

56.00

VVTA-615R

22

61.50

61.50

VVTA-680R

24

68.00

68.00

VVTA-735R

26

73.50

73.50

p.26

VVEA- 3 PIPES - TOP DISCHARGE


VVEA-250R

8

22.40

22.40

VVEA-280R

10

28.00

28.00

VVEA-335R

12

33.50

33.50

VVEA-400R

R410A

14

40.00

40.00

VVEA-450R

16

45.00

45.00

VVEA-504R

18

50.40

50.40

VVEA-560R

20

56.00

56.00

VVEA-615R

22

61.50

61.50

p.36

WATER FLOWLOGIC


VWVO-220R

8

22.40

25.00

VWVO-280R

R410A

10

28.00

31.50

VWVO-335R

12

33.50

37.50




VVFA

Compact VRF Range


Our range of compact VRFs adapts perfectly to any type of installation, commercial, tertiary or residential. The small dimensions offered by this range make it possible to considerably reduce handling operations, guaranteeing better adaptability in terms of installation (see installation characteristics).

► Twin rotary compressor

High efficiency compressor offering top performance with minimum vibration and reduced energy consumption.



► Two-stage subcooler



► DC Inverter fan motor



► Loading valve

► Eurovent certified



► Nsc up to 337% or SEER 8.5

COMPATIBLE



COMPATIBLE





VRF
Outdoor units

FlowLogic **V**

COMPATIBLE



COMPATIBLE



+ PRODUCT

- DC Inverter rotary compressor
- DC Inverter fan motor
- Integrated Human Machine Interface (HMI)
- Reduced dimension



RWV06
(optional, see configuration page 58)



RWV09
(optional, see configuration page 59)

FEATURES

TECHNOLOGY



DC INVERTER



BLUE FIN TREATMENT

INSTALLER FUNCTIONS



SELF DIAGNOSTIC



BMS COMPATIBLE



SERVICE MONITOR TOOL

CERTIFICATION

- AIRWELL participates in the ECP programme for AC1. Check ongoing validity of certificate: www.eurovent-certification.com



- All models are Eurovent certified, except VVFA080.

VVFA

2-pipes - Front discharge system



THE « SUSTAINABLE DEVELOPMENT »

- > Low consumption and optimized regulation for greater energy savings.

THE « USER »


- > Mode locking.
- > Centralised management.

THE « INSTALLER »

- > Up to 300 m of refrigeration network and 50 m of height difference.
- > Access to all parameters via the HMI (Human Machine Interface) for easier maintenance.

THE « TECHNOLOGY »

- > Up to 16 indoor units, performance certified by Eurovent* (8,10,12 HP).
- > Airconnect Pro: remote maintenance and management option (see page 8).



TECHNICAL DATA

MODEL		VVFA-125R-01M22	VVFA-150R-01M22	VVFA-150R-01T32	VVFA-220R-01T32	VVFA-280R-01T32	VVFA-335R-01T32
Part number		7VF150004	7VF150005	7VF150006	7VF150007	7VF150008	7VF150009
Phase		Single phase			Three phases		
Power	HP	4	6	6	8	10	12

COOLING MODE

Rated power*	kW	12.10	15.50	15.50	22.60	28.00	31.50
Rated power input	kW	2.99	4.31	4.31	6.46	8.75	10.16
EER		4.05	3.60	3.60	3.50	3.20	3.10
SEER		6.82	6.45	6.45	8.50	8.20	7.70
Seasonal operating limits	%	269.8	255	255	337	325	305

HEATING MODE

Rated power*	kW	14.20	18.00	18.00	22.60	30.50	31.50
Max. power	kW	-	-	-	25.00	32.00	35.00
Rated power input	kW	3.18	4.39	4.39	5.79	8.03	8.51
COP		4.47	4.10	4.10	3.90	3.80	3.70
SCOP*		3.92	3.8	3.8	5.00	4.80	4.70
Seasonal operating limits	%	153.8	149	149	197	189	185

POWER SUPPLY

Phase/Voltage/Frequency		1P/220-240V/50-60Hz	3P/380-415V/50-60Hz
-------------------------	--	---------------------	---------------------

INSTALLATION

Dimensions (WxHxD)	Unit	mm	950x1340x370			1050x1636x400		
	Shipping	mm	1023x1420x471			1150x1790x510		
Net weight/Gross weight	kg	108/123			149/168			
Compressor	Type	Rotary			Twin Rotary DCI			
	Engine power	W	4130	4130	4060	6270		
	Number of compressors		1			1		
Airflow (HS)	m ³ /h	7200			10000			
Sound pressure	Cooling mode	dB(A)	57	59	59	63	64	65
	Heating mode	dB(A)	57	59	59	65	66	67
Refrigerant		R410A			R410A			
Charge	kg	4.00			5.10			

PIPE LINE





Liquid pipe diameter	inches	3/8"			3/8"	3/8"	1/2"
Suction pipe diameter	inches	5/8"			3/4"	7/8"	1 1/8"
Max. length	m	300			300		
Max. length (equivalent/actual)	m	175/150			175/150		
Max. height between indoor and outdoor units	m	50			50		
Max. height between indoor units	m	15			15		
Indoor/outdoor unit power ratio (min./max.)	%	50-130			50-130		
Maximum number of connectable indoor units	quantity	8	13	13	13	16	19

OPERATING LIMITS

Cooling mode (min./max.)	°C	-5/50			-5/48	
Heating mode (min./max.)	°C	-20/27			-20/27	

* All the specifications are tested under nominal condition as per Eurovent conditions (in cooling mode: indoor temperature is 27°C DB/19°C WB, outdoor temperature 35°C DB/24°C WB; in heating mode: indoor temperature is 20°C DB, outdoor temperature is 7°C DB/6°C WB).

ACCESSORIES

ACCESSORY	PART NUMBER	REFERENCE	PHOTO	FUNCTION	COMMENT
Manifold pipe (gas + liquid)	7ACFHH001	TAU335		• Refrigerant gathering	• 33,5kW > Total indoor units power
	7ACFHH002	TAU506		• Refrigerant gathering	• 33,5kW ≤ Total indoor units power < 50,6kW
Central controller gateway and ModBus/RTU	7ACELH027	ADV05		• RWV06 and RWV08 adaptor and ModBus/RTU gateway	• See configuration page 61
Maintenance tool	7ACELH014	TD02		• Working parameters monitoring and recording tool	
Smart WiFi module	7ACEL1869	-		• Remote control by the smart WiFi module and controlled by the AirConnect Smart application	• Module dimensions: 86x86x12 mm.



VVTA

Reversible - Continuous heating 2-pipes VRF range

The 2-pipes VRF range was redesigned with a new innovative structure integrating a service door and all the electronic components mounted on a hinge.

- ▶ A unit capacity of up to 73.5 kW that can be coupled up to 4 modules.
- ▶ A new **4-way exchanger**, for better heat exchange.

COMPATIBLE




COMPATIBLE



▶ Innovative EVI compressor


We have equipped this new range with an EVI (enhanced vapor injection) compressor to offer Airwell customers a unique experience. The unit incorporates a compressor with EVI technology which increases the flow of refrigerant by 15% and thus obtains **a 30% improved efficiency in heating** compared to traditional compressors. In addition, thanks to the valve incorporated in the EVI compressor, **the efficiency of the system is increased by 5%** with operation down to -27°C in heating and up to $+52^{\circ}\text{C}$ in cooling.



► Continuous heating

The EVI compressor allows the production of heat without interruption during the defrosting phases.

The VVTA range uses intelligent defrosting technology, allowing heating production to be maintained even during defrosting phases. Indeed, an algorithm taking into account the pressure of the system, the temperature of the battery and influencing the variation of the fan motor allows us to offer this level of comfort by reducing the fluctuations of interior temperature.




► Modbus output included

No need for a gateway anymore to use a centralized controller or integrate the system with a BMS. An addressable and configurable Modbus output is directly available on the outdoor unit.




► Improved heating capacity

At low temperature, compared to standard machines, the heating capacity increases by 10%. In the 8HP unit for example, the heating capacity is 100% at -10°C outdoor temperature.



► A new 4-way heat exchanger

Improving heat transfer on the 4 sides of the condensing unit.





VRF
Outdoor units



COMPATIBLE



COMPATIBLE



+ PRODUCT

- Capacity from 25 to 294 kW
- Combination of 4 outdoor units possible
- Continuous heating
- EVI Scroll compressor
- Modbus outlet



RWV06
(optional, see
configuration
page 58)



RWV09
(optional, see
configuration
page 59)

FEATURES

TECHNOLOGY



DC INVERTER



BLUE FIN TREATMENT

INSTALLER FUNCTIONS



SELF DIAGNOSTIC



BMS COMPATIBLE



SERVICE MONITOR TOOL

CERTIFICATION

- AIRWELL participates in the ECP programme for AC1. Check ongoing validity of certificate:
www.eurovent-certification.com



VVTA

2 pipes - Top discharge system



VVTA 250-450



VVTA 504-735

THE + « SUSTAINABLE DEVELOPMENT »

- > Low consumption and optimized regulation for greater energy savings.
- > Improved efficiency at very low and very high temperature (from -27°C to 52°C) thanks to the EVI.

THE + « USER »

- > Heating mode uninterrupted during the defrost phases.
- > Intuitive and efficient centralized management.
- > Large choice of indoor units.

THE + « INSTALLER »

- > Improved accessibility, thanks to the service door.
- > Up to 1000 m of refrigeration network and 110 m of height difference.
- > Modbus outlet for easy BMS integration.
- > Access to all operating parameters, thanks to the HMI (Human Machine Interface).

THE + « TECHNOLOGY »

- > Automatic oil balance, no more balance tube.
- > Reinforced anti-corrosion treatment.
- > Compatible with AirConnect Pro and AirConnect Smart.
- > 110 Pa available static pressure on outdoor fan(s).

ACCESSORIES

ACCESSORY	PART NUMBER	REF.	PHOTO	FUNCTION	COMMENT
Gather pipe kit for 2 outdoor groups	7ACFHH013	TBS20		• Refrigerant gathering	• For 2 outdoor groups
Gather pipe kit for 3 outdoor groups	7ACFHH014	TBS30		• Refrigerant gathering	• For 3 outdoor groups
Gather pipe kit for 4 outdoor groups	7ACFHH014 + 7ACFHH015	TBS30 + TAU2040		• Refrigerant gathering	• For 4 outdoor groups
Manifold pipe (gas + liquid)	7ACFHH001	TAU335		• Refrigerant gathering	• 33,5 kW > Total IDU power
	7ACFHH002	TAU506		• Refrigerant gathering	• 33,5 kW ≤ Total IDU power < 50,6 kW
	7ACFHH003	TAU730		• Refrigerant gathering	• 50,6 kW ≤ Total IDU power < 73 kW
	7ACFHH004	TAU1350		• Refrigerant gathering	• 73 kW ≤ Total IDU power < 135 kW
	7ACFHH015	TAU2040		• Refrigerant gathering	• 135 kW ≤ Total IDU power
Maintenance tool	7ACELH014	TD02		• Working parameters monitoring and recording tool	
Smart WiFi module	7ACEL1869	-		• Remote control by the smart WiFi module and controlled by the AirConnect Smart application	• Module dimensions: 86x86x12 mm.

TECHNICAL DATA

VVTA

MODEL		VVTA-250R	VVTA-280R	VVTA-335R	VVTA-400R	VVTA-450R	VVTA-504R	VVTA-560R	VVTA-615R	VVTA-680R	VVTA-735R
Part number		7VFI50018	7VFI50019	7VFI50020	7VFI50021	7VFI50022	7VFI50023	7VFI50024	7VFI50025	7VFI50026	7VFI50027
Phase		Three phases									
Power	HP	8	10	12	14	16	18	20	22	24	26

COOLING MODE

Rated power*	kW	25.20	28.00	33.50	40.00	45.00	50.40	56.00	61.50	68.00	73.50
Rated power input	kW	6.24	7.37	9.31	11.94	13.24	15.70	16.62	18.30	21.94	24.75
Max. power input	kW	14.30	15.10	16.32	17.58	20.69	25.90	28.91	31.82	32.81	35.35
Rated current	A	10.53	12.44	15.71	20.16	22.34	26.51	28.05	30.90	31.42	35.87
Max. current	A	23.81	25.14	27.17	29.27	34.50	40.30	46.30	51.91	54.12	58.86
EER		4.04	3.80	3.60	3.35	3.40	3.21	3.37	3.36	3.10	2.97
SEER		7.25	7.09	6.69	6.60	6.36	6.78	6.75	6.54	5.97	5.68
Seasonal operating limits		287	281	265	261	251	268	267	259	236	224

HEATING MODE

Rated power*	kW	25.20	28.00	33.50	40.00	45.00	50.40	56.00	61.50	68.00	73.50
Rated power input	kW	5.56	6.32	7.71	9.71	10.92	12.81	14.23	16.14	18.86	21.62
Max. power input	kW	11.69	12.19	12.69	16.10	19.56	21.93	24.70	25.69	30.40	32.45
Rated current	A	9.67	10.99	13.40	16.88	18.99	22.27	24.75	28.06	32.80	37.60
Max. current	A	19.47	20.30	21.13	26.81	32.57	36.51	41.13	42.78	50.62	54.03
COP		4.53	4.43	4.35	4.12	4.12	3.93	3.93	3.81	3.61	3.40
SCOP		4.61	4.51	4.51	4.31	4.10	4.31	4.38	4.39	4.34	3.88
Seasonal operating limits		182	177	177	169	161	170	172	172	170	152

POWER SUPPLY

Phase/Voltage/Frequency		3P/380-415V/50-60Hz									
-------------------------	--	---------------------	--	--	--	--	--	--	--	--	--

PERFORMANCE

Airflow (HS)	m ³ /h	11000	11000	12000	13500	13500	17000	17000	18000	18000	19000	
Sound pressure	Cooling mode	dB(A)	61	61	61	64	64	64	64	-	-	-
	Heating mode	dB(A)	56	56	59	59	60	61	61	61	62	62
Sound power level (HS)	dB(A)	81	82	88	88	88	88	88	88	90	90	

INSTALLATION

External dimensions (WxHxD)	mm	980x1690x750					1410x1690x750				
Shipping dimensions (WxHxD)	mm	1070x1858x850					1515x1858x850				
Net weight/Gross weight	kg	255/280					385/410				
Compressor	Type	Scroll DCI					Scroll DCI				
	Brand	Mitsubishi Electric					Mitsubishi Electric				
	Number of compressors	1					2				

Refrigerant		R410A									
Charge	kg	10									
Liquid pipe diameter	inches	3/8"			1/2"			5/8"			
Suction pipe diameter	inches	3/4"	7/8"	1"		1 1/8"		1 1/8"			
Max. length	m	1000									
Max. length (equivalent/actual)	m	260/220									
Max. height between indoor and outdoor units (ODU down/up) (1)	m	110/90									
Standard height between indoor and outdoor units (ODU down/up) (2)	m	50/40									
Max. height between indoor units (3)	m	30									
Standard height between indoor units (4)	m	18									
External static pressure	Pa	110									
Indoor/outdoor unit power ratio (min./max.)	%	50~130									
Maximum number of connectable indoor units	quantity	13	16	20	24	27	30	33	36	40	43

OPERATING LIMITS

Cooling mode (min./max.)	°C	-5~52									
Heating mode (min./max.)	°C	-27~21									

(1) If the height difference between the outdoor and the indoor units is from 50 to 110m, you MUST contact your local distributor/dealer for individual design and production.

(2) Standard design and production in the factory.

(3) If the height difference between the indoor units is from 18 to 30m, you MUST contact your local distributor/dealer for individual design and production.

(4) Standard design and production in the factory.

* All the specifications are tested under nominal condition (in cooling mode: indoor temperature is 27°C DB/19°C WB, outdoor temperature 35°C DB/24WB; in heating mode: indoor temperature is 20°C DB, outdoor temperature is 7°C DB/6°CWB).

TECHNICAL DATA FOR TWO COMBINATIONS

MODEL		VVTA-800R	VVTA-850R	VVTA-900R	VVTA-954R	VVTA-1008R	VVTA-1064R	VVTA-1120R
COMBINATIONS		VVTA-400R	VVTA-400R	VVTA-450R	VVTA-450R	VVTA-504R	VVTA-504R	VVTA-560R
		7VF150021	7VF150021	7VF150022	7VF150022	7VF150023	7VF150023	7VF150024
		VVTA-400R	VVTA-450R	VVTA-450R	VVTA-504R	VVTA-504R	VVTA-560R	VVTA-560R
		7VF150021	7VF150022	7VF150022	7VF150023	7VF150023	7VF150024	7VF150024
Phase		Three phases						
Power	HP	28	30	32	34	36	38	40
COOLING MODE								
Rated power*	kW	80.00	85.00	90.00	95.40	100.80	106.40	112.00
Rated power input	kW	23.88	25.18	26.47	28.94	31.40	32.32	33.23
Max. power input	kW	35.16	38.27	41.38	46.59	51.80	54.81	57.82
Rated current	A	40.32	42.50	44.69	48.85	53.01	54.56	56.11
Max. current	A	58.54	69.00	80.60	92.60	103.82	108.24	117.72
EER		3.35	3.38	3.40	3.30	3.21	3.29	3.37
SEER		5.68	6.54	6.42	6.63	6.84	6.82	6.80
Seasonal operating limits		224	259	254	262	271	270	269
HEATING MODE								
Rated power*	kW	80.00	85.00	90.00	95.40	100.80	106.40	112.00
Rated power input	kW	19.42	20.63	21.84	23.73	25.62	27.04	28.47
Max. power input	kW	32.20	39.12	43.86	49.40	51.38	60.80	64.90
Rated current	A	33.76	35.87	37.98	41.27	44.55	47.02	49.50
Max. current	A	53.61	65.14	73.03	82.25	85.55	101.23	108.06
COP		4.12	4.12	4.12	4.01	3.93	3.93	3.93
SCOP		4.31	4.19	4.10	4.21	4.31	4.34	4.38
Seasonal operating limits		169	165	161	165	169	171	172
POWER SUPPLY								
Phase/Voltage/Frequency		3P/380-415V/50-60Hz						
PERFORMANCE								
Airflow (HS)	m ³ /h	27000	27000	27000	30500	34000	34000	34000
Sound pressure	Cooling mode	62	62.5	63	63.5	64	64	64
	Heating mode	62	62.5	63	63.5	64	64	64
Sound power level (HS)	dB(A)	91	91	91	91	91	91	91
INSTALLATION								
External dimensions (WxHxD)	mm	980x1690x750 + 980x1690x750			980x1690x750 + 1410x1690x750	1410x1690x750 + 1410x1690x750		
Shipping dimensions (WxHxD)	mm	1070x1858x850 + 1070x1858x850			1070x1858x850 + 1515x1858x850	1515x1858x850 + 1515x1858x850		
Net weight/Gross weight	kg	255/280 + 255/280			255/280 + 385/410	385/410 + 385/410		
Compressor	Type	Scroll DCI						
	Brand	Mitsubishi Electric						
	Number of compressors	2			3	4		
Refrigerant								
Charge	kg	R410A						
Liquid pipe diameter	inches	5/8"				3/4"		
Suction pipe diameter	inches	1 1/8	1 1/4			1 1/2		
Max. length	m				1000			
Max. length (equivalent/actual)	m				260/220			
Max. height between indoor and outdoor units (ODU down/up) (1)	m				110/90			
Standard height between indoor and outdoor units (ODU down/up) (2)	m				50/40			
Max. height between indoor units (3)	m				30			
Standard height between indoor units (4)	m				18			
External static pressure	Pa				110			
Indoor/outdoor unit power ratio (min./max.)	%				50-130			
Maximum number of connectable indoor units	quantity	47	50	53	56	59	63	64
OPERATING LIMITS								
Cooling mode (min./max.)	°C				-5~-52			
Heating mode (min./max.)	°C				-27~-21			

(1) If the height difference between the outdoor and the indoor units is from 50 to 110m, you MUST contact your local distributor/dealer for individual design and production.

(2) Standard design and production in the factory.

(3) If the height difference between the indoor units is from 18 to 30m, you MUST contact your local distributor/dealer for individual design and production.

(4) Standard design and production in the factory.

* All the specifications are tested under nominal condition (in cooling mode: indoor temperature is 27°C DB/19°C WB, outdoor temperature 35°C DB/24WB; in heating mode: indoor temperature is 20°C DB, outdoor temperature is 7°C DB/6°CWB).

TECHNICAL DATA FOR TWO COMBINATIONS

MODEL		VVTA-1175R	VVTA-1230R	VVTA-1295R	VVTA-1360R	VVTA-1415R	VVTA-1470R
COMBINATIONS		VVTA-560R	VVTA-615R	VVTA-615R	VVTA-680R	VVTA-680R	VVTA-735R
		7VF150024	7VF150025	7VF150025	7VF150026	7VF150026	7VF150027
		VVTA-615R	VVTA-615R	VVTA-680R	VVTA-680R	VVTA-735R	VVTA-735R
		7VF150025	7VF150025	7VF150026	7VF150026	7VF150027	7VF150027
Phase		<i>Three phases</i>					
Power	HP	42	44	46	48	50	52
COOLING MODE							
Rated power*	kW	117.50	123.00	129.50	136.00	141.50	147.00
Rated power input	kW	34.92	36.61	36.91	37.22	39.86	42.49
Max. power input	kW	60.73	63.64	64.63	65.62	68.16	70.70
Rated current	A	58.95	61.80	62.32	62.84	67.29	71.73
Max. current	A	117.08	138.00	161.20	185.20	207.64	216.48
EER		3.36	3.36	3.51	3.65	3.55	3.46
SEER		6.69	6.59	6.76	6.97	6.87	6.78
Seasonal operating limits		265	261	267	276	272	268
HEATING MODE							
Rated power*	kW	117.50	123.00	129.50	136.00	141.50	147.00
Rated power input	kW	30.37	32.27	35.00	37.73	40.49	43.25
Max. power input	kW	64.40	78.24	87.72	98.80	102.77	121.60
Rated current	A	52.81	56.12	60.86	65.60	70.40	75.20
Max. current	A	107.23	130.28	146.05	164.50	171.11	202.46
COP		3.86	3.81	3.69	3.60	3.49	3.39
SCOP		4.38	4.39	4.36	4.34	4.08	3.88
Seasonal operating limits		172	173	171	170	160	152
POWER SUPPLY							
Phase/Voltage/Frequency		3P/380-415V/50-60Hz					
PERFORMANCE							
Airflow (HS)	m ³ /h	35000	36000	36000	36000	37000	38000
Sound pressure	Cooling mode	dB(A)	64	64	64.5	65	65
	Heating mode	dB(A)	64	64	64.5	65	65
Sound power level (HS)	dB(A)	92	93	93	93	93	93
INSTALLATION							
External dimensions (WxHxD)	mm	1410x1690x750 + 1410x1690x750					
Shipping dimensions (WxHxD)	mm	1515x1858x850 + 1515x1858x850					
Net weight/Gross weight	kg	385/410 + 385/410					
Compressor	Type	Scroll DCI					
	Brand	Mitsubishi Electric					
	Number of compressors	4					
Refrigerant		R410A					
Charge	kg	20					
Liquid pipe diameter	inches	3/4"					
Suction pipe diameter	inches	1 1/2					
Max. length	m	1000					
Max. length (equivalent/actual)	m	260/220					
Max. height between indoor and outdoor units (ODU down/up) (1)	m	110/90					
Standard height between indoor and outdoor units (ODU down/up) (2)	m	50/40					
Max. height between indoor units (3)	m	30					
Standard height between indoor units (4)	m	18					
External static pressure	Pa	110					
Indoor/outdoor unit power ratio (min./max.)	%	50-130					
Maximum number of connectable indoor units	quantity	64					
OPERATING LIMITS							
Cooling mode (min./max.)	°C	-5/-52					
Heating mode (min./max.)	°C	-27/-21					

(1) If the height difference between the outdoor and the indoor units is from 50 to 110m, you MUST contact your local distributor/dealer for individual design and production.

(2) Standard design and production in the factory.

(3) If the height difference between the indoor units is from 18 to 30m, you MUST contact your local distributor/dealer for individual design and production.

(4) Standard design and production in the factory.

* All the specifications are tested under nominal condition (in cooling mode: indoor temperature is 27°C DB/19°C WB, outdoor temperature 35°C DB/24WB; in heating mode: indoor temperature is 20°C DB, outdoor temperature is 7°C DB/6°CWB).

TECHNICAL DATA FOR THREE COMBINATIONS

MODEL		VVTA-1512R	VVTA-1568R	VVTA-1624R	VVTA-1680R	VVTA-1735R	VVTA-1790R	VVTA-1845R	
COMBINATIONS		VVTA-504R	VVTA-504R	VVTA-504R	VVTA-560R	VVTA-615R	VVTA-615R	VVTA-615R	
		7VF150023	7VF150023	7VF150023	7VF150024	7VF150025	7VF150025	7VF150025	
		VVTA-504R	VVTA-504R	VVTA-560R	VVTA-560R	VVTA-560R	VVTA-615R	VVTA-615R	
		7VF150023	7VF150023	7VF150024	7VF150024	7VF150024	7VF150025	7VF150025	
		VVTA-504R	VVTA-560R	VVTA-560R	VVTA-560R	VVTA-560R	VVTA-560R	VVTA-615R	
	7VF150023	7VF150024	7VF150024	7VF150024	7VF150024	7VF150024	7VF150024	7VF150025	
Phase		Three phases							
Power	HP	54	56	58	60	62	64	66	
COOLING MODE									
Rated power*	kW	151.20	156.80	162.40	168.00	173.50	179.00	184.50	
Rated power input	kW	47.10	48.02	48.94	49.85	51.54	53.22	54.91	
Max. power input	kW	77.70	80.71	83.72	86.73	89.64	92.55	95.46	
Rated current	A	79.52	81.07	82.61	84.16	87.01	89.85	92.70	
Max. current	A	235.43	234.17	276.00	322.40	370.40	415.28	432.96	
EER		3.21	3.27	3.32	3.37	3.37	3.36	3.36	
SEER		6.85	6.84	6.83	6.81	6.74	6.67	6.60	
Seasonal operating limits		271	271	270	269	267	264	261	
HEATING MODE									
Rated power*	kW	151.20	156.80	162.40	168.00	173.50	179.00	184.50	
Rated power input	kW	38.43	39.85	41.27	42.70	44.60	46.51	48.41	
Max. power input	kW	129.80	128.80	156.48	175.44	197.60	205.54	243.20	
Rated current	A	66.82	69.30	71.77	74.25	77.56	80.87	84.18	
Max. current	A	216.12	214.45	260.56	292.11	329.00	342.22	404.93	
COP		3.93	3.93	3.93	3.93	3.88	3.84	3.81	
SCOP		4.31	4.33	4.36	4.38	4.38	4.39	4.39	
Seasonal operating limits		169	170	171	172	172	172	173	
POWER SUPPLY									
Phase/Voltage/Frequency		3P/380-415V/50-60Hz							
PERFORMANCE									
Airflow (HS)	m ³ /h	51000	51000	51000	51000	52000	53000	54000	
Sound pressure	Cooling mode	dB(A)	65.8	65.8	65.8	65.8	65.8	65.8	65.8
	Heating mode	dB(A)	65.8	65.8	65.8	65.8	65.8	65.8	65.8
Sound power level (HS)	dB(A)	93	93	93	93	93.5	94	95	
INSTALLATION									
External dimensions (WxHxD)	mm	1410x1690x750 + 1410x1690x750 + 1410x1690x750							
Shipping dimensions (WxHxD)	mm	1515x1858x850 + 1515x1858x850 + 1515x1858x850							
Net weight/Gross weight	kg	385/410 + 385/410 + 385/410							
Compressor	Type	Scroll DCI							
	Brand	Mitsubishi Electric							
	Number of compressors	6							
Refrigerant		R410A							
Charge	kg	30							
Liquid pipe diameter	inches	3/4"							
Suction pipe diameter	inches	1 1/2			1 5/8				
Max. length	m	1000							
Max. length (equivalent/actual)	m	260/220							
Max. height between indoor and outdoor units (ODU down/up) (1)	m	110/90							
Standard height between indoor and outdoor units (ODU down/up) (2)	m	50/40							
Max. height between indoor units (3)	m	30							
Standard height between indoor units (4)	m	18							
External static pressure	Pa	110							
Indoor/outdoor unit power ratio (min./max.)	%	50-130							
Maximum number of connectable indoor units	quantity	64							
OPERATING LIMITS									
Cooling mode (min./max.)	°C	-5~-52							
Heating mode (min./max.)	°C	-27~-21							

(1) If the height difference between the outdoor and the indoor units is from 50 to 110m, you MUST contact your local distributor/dealer for individual design and production.

(2) Standard design and production in the factory.

(3) If the height difference between the indoor units is from 18 to 30m, you MUST contact your local distributor/dealer for individual design and production.

(4) Standard design and production in the factory.

* All the specifications are tested under nominal condition (in cooling mode: indoor temperature is 27°C DB/19°C WB, outdoor temperature 35°C DB/24WB; in heating mode: indoor temperature is 20°C DB, outdoor temperature is 7°C DB/6°CWB).

TECHNICAL DATA FOR THREE COMBINATIONS

MODEL		VVTA-1910R	VVTA-19750R	VVTA-2040R	VVTA-2095R	VVTA-2150R	VVTA-2205R	
COMBINATIONS		VVTA-615R	VVTA-615R	VVTA-680R	VVTA-735R	VVTA-735R	VVTA-735R	
		7VF150025	7VF150025	7VF150026	7VF150027	7VF150027	7VF150027	
		VVTA-615R	VVTA-680R	VVTA-680R	VVTA-680R	VVTA-735R	VVTA-735R	
		7VF150025	7VF150026	7VF150026	7VF150026	7VF150027	7VF150027	
		VVTA-680R	VVTA-680R	VVTA-680R	VVTA-680R	VVTA-680R	VVTA-735R	
		7VF150026	7VF150026	7VF150026	7VF150026	7VF150026	7VF150027	
Phase		<i>Three phases</i>						
Power	HP	68	70	72	74	76	78	
COOLING MODE								
Rated power*	kW	191.00	197.50	204.00	209.50	215.00	220.50	
Rated power input	kW	55.22	55.53	55.83	58.47	61.10	63.74	
Max. power input	kW	96.45	97.44	98.43	100.97	103.51	106.05	
Rated current	A	93.22	93.74	94.26	98.71	103.15	107.60	
Max. current	A	470.86	468.33	552.00	644.80	740.80	830.56	
EER		3.46	3.56	3.65	3.58	3.52	3.46	
SEER		6.80	6.86	6.98	6.92	6.85	6.79	
Seasonal operating limits		269	271	276	274	271	269	
HEATING MODE								
Rated power*	kW	191.00	197.50	204.00	209.50	215.00	220.50	
Rated power input	kW	51.14	53.86	56.59	59.35	62.11	64.87	
Max. power input	kW	259.60	257.60	312.96	350.88	395.20	411.07	
Rated current	A	88.92	93.66	98.40	103.20	108.00	112.80	
Max. current	A	432.23	428.90	521.12	584.22	658.01	684.44	
COP		3.73	3.66	3.60	3.52	3.46	3.39	
SCOP		4.37	4.35	4.34	4.16	4.01	3.88	
Seasonal operating limits		172	171	170	164	157	152	
POWER SUPPLY								
Phase/Voltage/Frequency		3P/380-415V/50-60Hz						
PERFORMANCE								
Airflow (HS)	m³/h	54000	54000	54000	55000	56000	57000	
Sound pressure	Cooling mode	dB(A)	66	66.5	66.8	66.8	66.8	66.8
	Heating mode	dB(A)	66	66.5	66.8	66.8	66.8	66.8
Sound power level (HS)	dB(A)	95	95	95	95	95	95	
INSTALLATION								
External dimensions (WxHxD)	mm	1410x1690x750 + 1410x1690x750 + 1410x1690x750						
Shipping dimensions (WxHxD)	mm	1515x1858x850 + 1515x1858x850 + 1515x1858x850						
Net weight/Gross weight	kg	385/410 + 385/410 + 385/410						
Compressor	Type	Scroll DCI						
	Brand	Mitsubishi Electric						
	Number of compressors	6						
Refrigerant		R410A						
Charge	kg	30						
Liquid pipe diameter	inches	7/8"						
Suction pipe diameter	inches	1"3/4						
Max. length	m	1000						
Max. length (equivalent/actual)	m	260/220						
Max. height between indoor and outdoor units (ODU down/up) (1)	m	110/90						
Standard height between indoor and outdoor units (ODU down/up) (2)	m	50/40						
Max. height between indoor units (3)	m	30						
Standard height between indoor units (4)	m	18						
External static pressure	Pa	110						
Indoor/outdoor unit power ratio (min./max.)	%	50-130						
Maximum number of connectable indoor units	quantity	64						
OPERATING LIMITS								
Cooling mode (min./max.)	°C	-5~52						
Heating mode (min./max.)	°C	-27~21						

(1) If the height difference between the outdoor and the indoor units is from 50 to 110m, you MUST contact your local distributor/dealer for individual design and production.

(2) Standard design and production in the factory.

(3) If the height difference between the indoor units is from 18 to 30m, you MUST contact your local distributor/dealer for individual design and production.

(4) Standard design and production in the factory.

* All the specifications are tested under nominal condition (in cooling mode: indoor temperature is 27°C DB/19°C WB, outdoor temperature 35°C DB/24WB; in heating mode: indoor temperature is 20°C DB, outdoor temperature is 7°C DB/6°CWB).

TECHNICAL DATA FOR FOUR COMBINATIONS

MODEL		VVTA-2240R	VVTA-2295R	VVTA-2350R	VVTA-2405R	VVTA-2460R	VVTA-2525R	VVTA-2590R	
COMBINATIONS		VVTA-560R	VVTA-560R	VVTA-560R	VVTA-560R	VVTA-615R	VVTA-680R	VVTA-680R	
		7VF150024	7VF150024	7VF150024	7VF150024	7VF150025	7VF150026	7VF150026	
		VVTA-560R	VVTA-560R	VVTA-560R	VVTA-615R	VVTA-615R	VVTA-615R	VVTA-680R	
		7VF150024	7VF150024	7VF150024	7VF150025	7VF150025	7VF150025	7VF150026	
		VVTA-560R	VVTA-560R	VVTA-615R	VVTA-615R	VVTA-615R	VVTA-615R	VVTA-615R	
		7VF150024	7VF150024	7VF150025	7VF150025	7VF150025	7VF150025	7VF150025	
		VVTA-560R	VVTA-615R	VVTA-615R	VVTA-615R	VVTA-615R	VVTA-615R	VVTA-615R	
		7VF150024	7VF150025	7VF150025	7VF150025	7VF150025	7VF150025	7VF150025	
Phase		Three phases							
Power	HP	80	82	84	86	88	90	92	
COOLING MODE									
Rated power*	kW	224.00	229.50	235.00	240.50	246.00	252.50	259.00	
Rated power input	kW	66.47	68.16	69.84	71.53	73.21	73.52	73.83	
Max. power input	kW	115.64	118.55	121.46	124.37	127.28	128.27	129.26	
Rated current	A	112.21	115.06	117.91	120.75	123.60	124.12	124.64	
Max. current	A	865.92	941.72	936.66	1104.00	1289.60	1481.60	1661.12	
EER		3.37	3.37	3.36	3.36	3.36	3.43	3.51	
SEER		6.82	6.76	6.71	6.65	6.61	6.70	6.80	
Seasonal operating limits		270	267	265	263	261	265	269	
HEATING MODE									
Rated power*	kW	224.00	229.50	235.00	240.50	246.00	252.50	259.00	
Rated power input	kW	56.93	58.84	60.74	62.65	64.55	67.28	70.00	
Max. power input	kW	486.40	519.20	515.20	625.92	701.76	790.40	822.14	
Rated current	A	98.99	102.31	105.62	108.93	112.24	116.98	121.72	
Max. current	A	809.86	864.47	857.81	1042.24	1168.43	1316.02	1368.87	
COP		3.93	3.90	3.86	3.83	3.81	3.75	3.69	
SCOP		4.38	4.38	4.38	4.39	4.39	4.38	4.36	
Seasonal operating limits		172	172	172	173	173	172	171	
POWER SUPPLY									
Phase/Voltage/Frequency		3P/380-415V/50-60Hz							
PERFORMANCE									
Airflow (HS)	m ³ /h	68000	69000	70000	71000	72000	72000	72000	
Sound pressure	Cooling mode	dB(A)	67	67	67	67	67.5	67.5	
	Heating mode	dB(A)	67	67	67	67	67.5	67.5	
Sound power level (HS)	dB(A)	94	95	95	96	96	96	96	
INSTALLATION									
External dimensions (WxHxD)	mm	1410x1690x750 + 1410x1690x750 + 1410x1690x750 + 1410x1690x750							
Shipping dimensions (WxHxD)	mm	1515x1858x850 + 1515x1858x850 + 1515x1858x850 + 1515x1858x850							
Net weight/Gross weight	kg	385/410 + 385/410 + 385/410 + 385/410							
Compressor	Type	Scroll DCI							
	Brand	Mitsubishi Electric							
	Number of compressors	8							
Refrigerant									
Charge	kg	R410A 40							
Liquid pipe diameter	inches	7/8"				1"			
Suction pipe diameter	inches	1"3/4				2"			
Max. length	m	1000							
Max. length (equivalent/actual)	m	260/220							
Max. height between indoor and outdoor units (ODU down/up) (1)	m	110/90							
Standard height between indoor and outdoor units (ODU down/up) (2)	m	50/40							
Max. height between indoor units (3)	m	30							
Standard height between indoor units (4)	m	18							
External static pressure	Pa	110							
Indoor/outdoor unit power ratio (min./max.)	%	50-130							
Maximum number of connectable indoor units	quantity	64							
OPERATING LIMITS									
Cooling mode (min./max.)	°C	-5~-52							
Heating mode (min./max.)	°C	-27~-21							

(1) If the height difference between the outdoor and the indoor units is from 50 to 110m, you MUST contact your local distributor/dealer for individual design and production.

(2) Standard design and production in the factory.

(3) If the height difference between the indoor units is from 18 to 30m, you MUST contact your local distributor/dealer for individual design and production.

(4) Standard design and production in the factory.

* All the specifications are tested under nominal condition (in cooling mode: indoor temperature is 27°C DB/19°C WB, outdoor temperature 35°C DB/24°C WB; in heating mode: indoor temperature is 20°C DB, outdoor temperature is 7°C DB/6°C WB).

TECHNICAL DATA FOR FOUR COMBINATIONS

MODEL		VVTA-2655R	VVTA-2720R	VVTA-2775R	VVTA-2830R	VVTA-2885R	VVTA-2940R	
COMBINATIONS	VVTA-680R	VVTA-680R	VVTA-680R	VVTA-735R	VVTA-735R	VVTA-735R	VVTA-735R	
	7VF150026	7VF150026	7VF150026	7VF150027	7VF150027	7VF150027	7VF150027	
	VVTA-680R	VVTA-680R	VVTA-680R	VVTA-680R	VVTA-735R	VVTA-735R	VVTA-735R	
	7VF150026	7VF150026	7VF150026	7VF150026	7VF150027	7VF150027	7VF150027	
	VVTA-680R	VVTA-680R	VVTA-680R	VVTA-680R	VVTA-680R	VVTA-735R	VVTA-735R	
	7VF150026	7VF150026	7VF150026	7VF150026	7VF150026	7VF150027	7VF150027	
	VVTA-615R	VVTA-680R	VVTA-680R	VVTA-680R	VVTA-680R	VVTA-680R	VVTA-735R	
	7VF150025	7VF150026	7VF150026	7VF150026	7VF150026	7VF150026	7VF150027	
Phase		<i>Three phases</i>						
Power	HP	94	96	98	100	102	104	
COOLING MODE								
Rated power*	kW	265.50	272.00	277.50	283.00	288.50	294.00	
Rated power input	kW	74.14	74.44	77.08	79.71	82.35	84.98	
Max. power input	kW	130.25	131.24	133.78	136.32	138.86	141.40	
Rated current	A	125.16	125.68	130.13	134.57	139.02	143.47	
Max. current	A	1731.84	1883.45	1873.33	2208.00	2579.20	2963.20	
EER		3.58	3.65	3.60	3.55	3.50	3.46	
SEER		6.90	6.99	6.94	6.89	6.84	6.80	
Seasonal operating limits		273	277	275	273	271	269	
HEATING MODE								
Rated power*	kW	265.50	272.00	277.50	283.00	288.50	294.00	
Rated power input	kW	72.73	75.45	78.21	80.97	83.73	86.50	
Max. power input	kW	972.80	1038.40	1030.40	1251.84	1403.52	1580.80	
Rated current	A	126.46	131.20	136.00	140.80	145.60	150.40	
Max. current	A	1619.71	1728.94	1715.62	2084.48	2336.86	2632.03	
COP		3.65	3.60	3.54	3.49	3.44	3.39	
SCOP		4.35	4.34	4.20	4.08	3.98	3.88	
Seasonal operating limits		171	170	165	160	156	152	
POWER SUPPLY								
Phase/Voltage/Frequency		3P/380-415V/50-60Hz						
PERFORMANCE								
Airflow (HS)	m ³ /h	72000	72000	73000	74000	75000	76000	
Sound pressure	Cooling mode	dB(A)	68	68	68	68	68	68
	Heating mode	dB(A)	68	68	68	68	68	68
Sound power level (HS)	dB(A)	96	96	96	96	96	96	
INSTALLATION								
External dimensions (WxHxD)	mm	1410x1690x750 + 1410x1690x750 + 1410x1690x750 + 1410x1690x750						
Shipping dimensions (WxHxD)	mm	1485x1858x850 + 1485x1858x850 + 1485x1858x850 + 1485x1858x850						
Net weight/Gross weight	kg	385/410 + 385/410 + 385/410 + 385/410						
Compressor	Type	Scroll DCI						
	Brand	Mitsubishi Electric						
	Number of compressors	8						
Refrigerant		R410A						
Charge	kg	40						
Liquid pipe diameter	inches	1"						
Suction pipe diameter	inches	2"		2"1/4				
Max. length	m	1000						
Max. length (equivalent/actual)	m	260/220						
Max. height between indoor and outdoor units (ODU down/up) (1)	m	110/90						
Standard height between indoor and outdoor units (ODU down/up) (2)	m	50/40						
Max. height between indoor units (3)	m	30						
Standard height between indoor units (4)	m	18						
External static pressure	Pa	110						
Indoor/outdoor unit power ratio (min./max.)	%	50-130						
Maximum number of connectable indoor units	quantity	64						
OPERATING LIMITS								
Cooling mode (min./max.)	°C	-5~-52						
Heating mode (min./max.)	°C	-27~-21						

(1) If the height difference between the outdoor and the indoor units is from 50 to 110m, you MUST contact your local distributor/dealer for individual design and production.

(2) Standard design and production in the factory.

(3) If the height difference between the indoor units is from 18 to 30m, you MUST contact your local distributor/dealer for individual design and production.

(4) Standard design and production in the factory.

* All the specifications are tested under nominal condition (in cooling mode: indoor temperature is 27°C DB/19°C WB, outdoor temperature 35°C DB/24WB; in heating mode: indoor temperature is 20°C DB, outdoor temperature is 7°C DB/6°CWB).



VVEA

3-pipes energy recovery VRF range



- ▶ New range, new structure, new selection boxes.
- ▶ Just like the version of our VVTA range, the new VVEA 3-tube energy recovery VRF features the new structure of the range, as well as the **4-way heat exchanger** for a performance always at the highest level.
- ▶ Offering a wide range of capacity with mono-modules with a capacity of 61.5 kW and a possible coupling of 4 outdoor units, the new VVEA will meet all hotel, office and tertiary application needs.



Commerces



Hôtels



Bureaux

COMPATIBLE



COMPATIBLE



▶ Modbus output included


No need for a gateway anymore to use a centralized controller or integrate the system with a BMS. An addressable and configurable Modbus output is directly available on the outdoor unit.



► **New selection boxes**


They incorporate **electronic expansion valves** replacing the old slide valves for much **quieter** operation and regulation perfectly suited to the needs of the connected indoor units.

In addition, the new selection boxes are equipped with **3 additional tubes** at the output, allowing it to be put in series for unprecedented modularity. This is valid for boxes with 4 outlets.



MODEL	PART NUMBER	MAXIMUM CONNECTABLE CAPACITY (kW)	POWER SUPPLY	MAXIMUM NUMBER OF CONNECTABLE INDOOR UNITS (same operation mode)	DIMENSIONS (mm)
VVEA HR 112 KIT	7ACELH028	< 11.2	1P/220-240V/50-60Hz	5	388x200x277
VVEA HR 180 KIT	7ACELH029	< 18	1P/220-240V/50-60Hz	8	388x200x277
VVEA HR 280 KIT	7ACELH030	< 28	1P/220-240V/50-60Hz	8	388x200x277
VVEA HR 450 KIT (4 outlets)	7ACELH031	< 45	1P/220-240V/50-60Hz	20	405x300x421
	Total for 4 outlets		Total by outlet		
	Total capacity of indoor units	Quantity of indoor units	Total capacity of indoor units	Quantity of indoor units	
	≤ 45 kW	≤ 20	≤ 11,2 kW	≤ 5	

The limit of the input power of a series is 71 kW maximum*.





VRF
Outdoor units

FlowLogic **V**

COMPATIBLE



COMPATIBLE



+ PRODUCT

- Capacity from 22.4 to 246 kW
- Combination of 4 outdoor units possible
- New selection boxes
- New 4-way heat exchanger
- Modbus outlet



RWV06
(optional, see configuration page 58)



RWV09
(optional, see configuration page 59)

FEATURES

TECHNOLOGY



DC INVERTER



BLUE FIN TREATMENT

INSTALLER FUNCTIONS



SELF DIAGNOSTIC



BMS COMPATIBLE



SERVICE MONITOR TOOL

CERTIFICATION

- AIRWELL participates in the ECP programme for AC1. Check ongoing validity of certificate: www.eurovent-certification.com



VVEA

3-pipes with heat recovery



VVEA 250-450



VVEA 504-735

THE + « SUSTAINABLE DEVELOPMENT »

- > Heat recovery between units, for better energy efficiency.

THE + « USER »

- > Simultaneous operating in heating and cooling modes.
- > New even quieter selection box, thanks to their electronic expansion valve.

THE + « INSTALLER »

- > New improved accessibility, thanks to the service door.
- > Up to 1000 m of refrigeration network and 110 m of height difference.
- > Modbus outlet for easy BMS integration.
- > Access to all operating parameters, thanks to the HMI (Human Machine Interface).

THE + « TECHNOLOGY »

- > New 4-way selection boxes in series with reversible orientation.
- > Automatic oil balance, no need for a balance tube.
- > Reinforced anti-corrosion treatment.
- > Compatible with AirConnect Pro and AirConnect Smart.

ACCESSORIES

ACCESSORY	PART NUMBER	REF.	PHOTO	FUNCTION	COMMENT
Gather pipe kit for 2 outdoor groups	7ACELH041	TBS20HR		• Refrigerant gathering	• For 2 outdoor groups
Gather pipe kit for 3 outdoor groups	7ACELH042	TBS30HR		• Refrigerant gathering	• For 3 outdoor groups
Gather pipe kit for 4 outdoor groups	7ACELH043	TBS40HR		• Refrigerant gathering	• For 4 outdoor groups
Manifold pipe (gas + liquid)	7ACFHH007	TAU335HR		• Refrigerant gathering	• 33,5 kW > Total IDU power
	7ACFHH008	TAU506HR		• Refrigerant gathering	• 33,5 kW ≤ Total IDU power < 50,6 kW
	7ACFHH009	TAU730HR		• Refrigerant gathering	• 50,6 kW ≤ Total IDU power < 73 kW
	7ACFHH010	TAU1350HR		• Refrigerant gathering	• 73 kW ≤ Total IDU power < 135 kW
	7ACELH044	TAU2040HR		• Refrigerant gathering	• 135 kW ≤ Total IDU power
Maintenance tool	7ACELH014	TD02		• Working parameters monitoring and recording tool	
Smart WiFi module	7ACEL1869	-		• Remote control by the smart WiFi module and controlled by the AirConnect Smart application	• Module dimensions: 86x86x12 mm.

TECHNICAL DATA

MODEL		VVEA-250R	VVEA-280R	VVEA-335R	VVEA-400R	VVEA-450R	VVEA-504R	VVEA-560R	VVEA-615R
Part number		7VF150010	7VF150011	7VF150012	7VF150013	7VF150014	7VF150015	7VF150016	7VF150017
Phase		<i>Three phases</i>							
Power	HP	8	10	12	14	16	18	20	22
COOLING MODE									
Rated power*	kW	22.40	28.00	33.50	40.00	45.00	50.40	56.00	61.50
Rated power input	kW	5.63	7.67	9.57	12.31	14.06	16.13	17.23	20.00
Max. power input	kW	12.80	13.80	18.20	19.20	25.10	28.50	32.00	33.00
Rated current	A	9.29	12.67	15.81	20.33	23.22	26.64	28.46	33.03
Max. current	A	21.14	22.79	30.06	31.71	41.45	47.07	52.85	54.50
EER		3.98	3.65	3.50	3.25	3.20	3.12	3.25	3.08
SEER		7.05	6.68	6.58	6.37	6.86	6.48	5.90	5.74
Seasonal operating limits		279	264	260	252	271	256	233	227
HEATING MODE									
Rated power*	kW	22.40	28.00	33.50	40.00	45.00	50.40	56.00	61.50
Rated power input	kW	5.15	6.67	8.38	10.53	11.39	13.70	15.78	17.91
Max. power input	kW	11.50	12.50	17.40	18.40	22.70	25.50	29.40	30.40
Rated current	A	8.50	11.01	13.83	17.38	18.81	22.62	26.05	29.58
Max. current	A	18.99	20.64	28.74	30.39	37.49	42.11	48.55	50.21
COP		4.35	4.20	4.00	3.80	3.95	3.68	3.55	3.43
SCOP		4.02	3.94	4.08	3.86	4.21	3.99	3.93	3.76
Seasonal operating limits		158	155	160	151	165	157	154	147
POWER SUPPLY									
Phase/Voltage/Frequency		3P/380-415V/50-60Hz							
PERFORMANCE									
Airflow (HS)	m ³ /h	12000	12000	13500	13500	17000	17000	19000	19000
Sound pressure (HS)	dB(A)	57.00	58.00	60.00	61.00	62.00	63.00	63.00	64.00
INSTALLATION									
External dimensions (WxHxD)	mm	980x1690x750				1410x1690x750			
Shipping dimensions (WxHxD)	mm	1070x1858x850				1515x1858x850			
Net weight/Gross weight	kg	246/271		257/282		366/395		375/404	
Compressor	Type	Scroll DCI				Scroll DCI			
	Brand	Mitsubishi Electric				Mitsubishi Electric			
	Number of compressors	1				2			
Refrigerant									
Charge	kg	R410A 10							
Liquid pipe diameter	inches	3/8"		1/2"		5/8"			
Suction pipe diameter	inches	3/4"	7/8"	1"		1 1/8"			
Suction pipe diameter haut	inches	3/4"		7/8"		1"			
Max. length	m	1000							
Max. length (equivalent/actual)	m	260/220							
Max. height between indoor and outdoor units (ODU down/up) (1)	m	110/90							
Standard height between indoor and outdoor units (ODU down/up) (2)	m	50/40							
Max. height between indoor units (3)	m	30							
Standard height between indoor units (4)	m	18							
External static pressure	Pa	110							
Indoor/outdoor unit power ratio (min./max.)	%	50~130							
Maximum number of connectable indoor units	quantity	13	16	20	24	27	30	33	36
OPERATING LIMITS									
Cooling mode (min./max.)	°C	-5~50							
Heating mode (min./max.)	°C	-23~21							

(1) If the height difference between the outdoor and the indoor units is from 50 to 110m, you MUST contact your local distributor/dealer for individual design and production.

(2) Standard design and production in the factory.

(3) If the height difference between the indoor units is from 18 to 30m, you MUST contact your local distributor/dealer for individual design and production.

(4) Standard design and production in the factory.

* All the specifications are tested under nominal condition (in cooling mode: indoor temperature is 27°C DB/19°C WB, outdoor temperature 35°C DB/24WB; in heating mode: indoor temperature is 20°C DB, outdoor temperature is 7°C DB/6°CWB).

TECHNICAL DATA FOR TWO COMBINATIONS

MODEL		VVEA-670R	VVEA-735R	VVEA-800R	VVEA-850R
COMBINATIONS		VVEA-335R	VVEA-335R	VVEA-400R	VVEA-400R
		7VF150012	7VF150012	7VF150013	7VF150013
		VVEA-335R	VVEA-400R	VVEA-400R	VVEA-450R
		7VF150012	7VF150013	7VF150013	7VF150014
Phase		Three phases			
Power	HP	24	26	28	30
COOLING MODE					
Rated power*	kW	67.00	73.50	80.00	85.00
Rated power input	kW	19.14	21.88	24.62	26.37
Max. power input	kW	36.40	37.40	38.40	44.30
Rated current	A	31.61	36.13	40.65	43.55
Max. current	A	60.11	61.77	63.42	73.16
EER		3.50	3.36	3.25	3.22
SEER		6.58	6.46	6.37	6.61
Seasonal operating limits		260	255	252	261
HEATING MODE					
Rated power*	kW	67.00	73.50	80.00	85.00
Rated power input	kW	16.75	18.90	21.05	21.92
Max. power input	kW	34.80	35.80	36.80	41.10
Rated current	A	27.66	31.22	34.77	36.20
Max. current	A	57.47	59.12	60.78	67.88
COP		4.00	3.89	3.80	3.88
SCOP		4.08	3.94	3.86	4.02
Seasonal operating limits		160	155	151	158
POWER SUPPLY					
Phase/Voltage/Frequency		3P/380-415V/50-60Hz			
PERFORMANCE					
Airflow (HS)	m ³ /h	27000	27000	27000	30500
Sound pressure (HS)	dB(A)	63.00	63.50	64.00	64.50
INSTALLATION					
External dimensions (WxHxD)	mm	980x1690x750 + 980x1690x750			980x1690x750 + 1410x1690x750
Shipping dimensions (WxHxD)	mm	1070x1858x850 + 1070x1858x850			1070x1858x850 + 1515x1858x850
Net weight/Gross weight	kg	246/271 + 246/271			246/271 + 366/395
Compressor	Type	Scroll DCI			
	Brand	Mitsubishi Electric			
	Number of compressors	2			
Refrigerant					
		R410A			
Charge	kg	20			
Liquid pipe diameter	inches	5/8"			3/4"
Suction pipe diameter	inches	1 1/8"			1 1/4"
Suction pipe diameter haut	inches	1"			1 1/8"
Max. length	m	1000			
Max. length (equivalent/actual)	m	260/220			
Max. height between indoor and outdoor units (ODU down/up) (1)	m	110/90			
Standard height between indoor and outdoor units (ODU down/up) (2)	m	50/40			
Max. height between indoor units (3)	m	30			
Standard height between indoor units (4)	m	18			
External static pressure	Pa	110			
Indoor/outdoor unit power ratio (min./max.)	%	50-130			
Maximum number of connectable indoor units	quantity	40	43	47	50
OPERATING LIMITS					
Cooling mode (min./max.)	°C	-5-52			
Heating mode (min./max.)	°C	-27-21			

(1) If the height difference between the outdoor and the indoor units is from 50 to 110m, you MUST contact your local distributor/dealer for individual design and production.

(2) Standard design and production in the factory.

(3) If the height difference between the indoor units is from 18 to 30m, you MUST contact your local distributor/dealer for individual design and production.

(4) Standard design and production in the factory.

* All the specifications are tested under nominal condition (in cooling mode: indoor temperature is 27°C DB/19°C WB, outdoor temperature 35°C DB/24WB; in heating mode: indoor temperature is 20°C DB, outdoor temperature is 7°C DB/6°CWB).

TECHNICAL DATA FOR TWO COMBINATIONS

MODEL	VVEA-900R	VVEA-954R	VVEA-1008R	VVEA-1064R	VVEA-1120R	VVEA-1175R	VVEA-1230R	
COMBINATIONS	VVEA-450R	VVEA-450R	VVEA-504R	VVEA-504R	VVEA-560R	VVEA-560R	VVEA-615R	
	7VF150014	7VF150014	7VF150015	7VF150015	7VF150016	7VF150016	7VF150017	
	VVEA-450R	VVEA-504R	VVEA-504R	VVEA-560R	VVEA-560R	VVEA-615R	VVEA-615R	
	7VF150014	7VF150015	7VF150015	7VF150016	7VF150016	7VF150017	7VF150017	
Phase	Three phases							
Power	HP	32	34	36	38	40	42	44
COOLING MODE								
Rated power*	kW	90.00	95.40	100.80	106.40	112.00	117.50	123.00
Rated power input	kW	28.13	30.19	32.26	33.36	34.46	37.23	40.00
Max. power input	kW	50.20	53.60	57.00	60.50	64.00	65.00	66.00
Rated current	A	46.45	49.86	53.27	55.09	56.91	61.49	66.06
Max. current	A	82.91	88.52	94.14	99.92	105.70	107.35	109.00
EER		3.20	3.16	3.12	3.19	3.25	3.16	3.08
SEER		6.86	6.64	6.48	6.15	5.90	5.81	5.74
Seasonal operating limits		271	263	256	243	233	229	227
HEATING MODE								
Rated power*	kW	90.00	95.40	100.80	106.40	112.00	117.50	123.00
Rated power input	kW	22.78	25.09	27.40	29.47	31.55	33.69	35.82
Max. power input	kW	45.40	48.20	51.00	54.90	58.80	59.80	60.80
Rated current	A	37.63	41.44	45.25	48.68	52.11	55.63	59.16
Max. current	A	74.98	79.60	84.23	90.67	97.11	98.76	100.41
COP		3.95	3.80	3.68	3.61	3.55	3.49	3.43
SCOP		4.21	4.08	3.99	3.96	3.93	3.83	3.76
Seasonal operating limits		165	160	157	155	154	150	147
POWER SUPPLY								
Phase/Voltage/Frequency		3P/380-415V/50-60Hz						
PERFORMANCE								
Airflow (HS)	m ³ /h	34000	34000	34000	36000	38000	38000	38000
Sound pressure (HS)	dB(A)	65.00	65.50	66.00	66.00	66.00	66.50	67.00
INSTALLATION								
External dimensions (WxHxD)	mm	1410x1690x750 + 1410x1690x750						
Shipping dimensions (WxHxD)	mm	1515x1858x850 + 1515x1858x850						
Net weight/Gross weight	kg	366/395 + 366/395			366/395 + 375/404		375/404 + 375/404	
Compressor	Type	Scroll DCI						
	Brand	Mitsubishi Electric						
	Number of compressors	4						
Refrigerant		R410A						
Charge	kg	20						
Liquid pipe diameter	inches	3/4"						
Suction pipe diameter	inches	1"1/4			1"1/2			
Suction pipe diameter haut	inches	1"1/8			1"3/8			
Max. length	m	1000						
Max. length (equivalent/actual)	m	260/220						
Max. height between indoor and outdoor units (ODU down/up) (1)	m	110/90						
Standard height between indoor and outdoor units (ODU down/up) (2)	m	50/40						
Max. height between indoor units (3)	m	30						
Standard height between indoor units (4)	m	18						
External static pressure	Pa	110						
Indoor/outdoor unit power ratio (min./max.)	%	50~130						
Maximum number of connectable indoor units	quantity	53	56	59	63	64	64	64
OPERATING LIMITS								
Cooling mode (min./max.)	°C	-5~52						
Heating mode (min./max.)	°C	-27~21						

(1) If the height difference between the outdoor and the indoor units is from 50 to 110m, you MUST contact your local distributor/dealer for individual design and production.

(2) Standard design and production in the factory.

(3) If the height difference between the indoor units is from 18 to 30m, you MUST contact your local distributor/dealer for individual design and production.

(4) Standard design and production in the factory.

* All the specifications are tested under nominal condition (in cooling mode: indoor temperature is 27°C DB/19°C WB, outdoor temperature 35°C DB/24WB; in heating mode: indoor temperature is 20°C DB, outdoor temperature is 7°C DB/6°CWB).

TECHNICAL DATA FOR THREE COMBINATIONS

MODEL		VVEA-1300R	VVEA-1350R	VVEA-1404R	VVEA-1458R	VVEA-1512R	VVEA-1568R
COMBINATIONS		VVEA-400R	VVEA-450R	VVEA-450R	VVEA-450R	VVEA-504R	VVEA-504R
		7VF150013	7VF150014	7VF150014	7VF150014	7VF150015	7VF150015
		VVEA-450R	VVEA-450R	VVEA-450R	VVEA-504R	VVEA-504R	VVEA-504R
		7VF150014	7VF150014	7VF150014	7VF150015	7VF150015	7VF150015
		VVEA-450R	VVEA-450R	VVEA-504R	VVEA-504R	VVEA-504R	VVEA-560R
		7VF150014	7VF150014	7VF150015	7VF150015	7VF150015	7VF150016
Phase		Three phases					
Power	HP	46	48	50	52	54	56
COOLING MODE							
Rated power*	kW	130.00	135.00	140.40	145.80	151.20	156.80
Rated power input	kW	40.43	42.19	44.25	46.32	48.39	49.49
Max. power input	kW	69.40	75.30	78.70	82.10	85.50	89.00
Rated current	A	66.77	69.67	73.09	76.50	79.91	81.73
Max. current	A	114.61	124.36	129.97	135.59	141.20	146.98
EER		3.22	3.20	3.17	3.15	3.12	3.17
SEER		6.70	6.86	6.70	6.58	6.48	6.25
Seasonal operating limits		265	271	265	260	256	247
HEATING MODE							
Rated power*	kW	130.00	135.00	140.40	145.80	151.20	156.80
Rated power input	kW	33.31	34.18	36.48	38.79	41.10	43.17
Max. power input	kW	63.80	68.10	70.90	73.70	76.50	80.40
Rated current	A	55.01	56.44	60.25	64.06	67.87	71.30
Max. current	A	105.37	112.47	117.09	121.72	126.34	132.78
COP		3.90	3.95	3.85	3.76	3.68	3.63
SCOP		4.08	4.21	4.12	4.05	3.99	3.97
Seasonal operating limits		160	165	162	159	157	156
POWER SUPPLY							
Phase/Voltage/Frequency		3P/380-415V/50-60Hz					
PERFORMANCE							
Airflow (HS)	m ³ /h	51000	51000	51000	51000	53000	30500
Sound pressure (HS)	dB(A)	67.00	67.00	67.50	68.00	68.00	64.50
INSTALLATION							
External dimensions (WxHxD)	mm	980x1690x750 + 980x1690x750 + 980x1690x750	1410x1690x750 + 1410x1690x750 + 1410x1690x750				
Shipping dimensions (WxHxD)	mm	1070x1858x850 + 1515x1858x850 + 1515x1858x850	1515x1858x850 + 1515x1858x850 + 1515x1858x850				
Net weight/Gross weight	kg	257/282 + 366/395 + 366/395	366/395 + 366/395 + 366/395				366/395 + 366/395 + 375/404
Compressor	Type	Scroll DCI					
	Brand	Mitsubishi Electric					
	Number of compressors	5	6				
Refrigerant							
		R410A					
Charge	kg	30					
Liquid pipe diameter	inches	3/4"					
Suction pipe diameter	inches	1 1/2					
Suction pipe diameter haut	inches	1 3/8					
Max. length	m	1000					
Max. length (equivalent/actual)	m	260/220					
Max. height between indoor and outdoor units (ODU down/up) (1)	m	110/90					
Standard height between indoor and outdoor units (ODU down/up) (2)	m	50/40					
Max. height between indoor units (3)	m	30					
Standard height between indoor units (4)	m	18					
External static pressure	Pa	110					
Indoor/outdoor unit power ratio (min./max.)	%	50-130					
Maximum number of connectable indoor units	quantity	64					
OPERATING LIMITS							
Cooling mode (min./max.)	°C	-5~-52					
Heating mode (min./max.)	°C	-27~-21					

(1) If the height difference between the outdoor and the indoor units is from 50 to 110m, you MUST contact your local distributor/dealer for individual design and production.

(2) Standard design and production in the factory.

(3) If the height difference between the indoor units is from 18 to 30m, you MUST contact your local distributor/dealer for individual design and production.

(4) Standard design and production in the factory.

* All the specifications are tested under nominal condition (in cooling mode: indoor temperature is 27°C DB/19°C WB, outdoor temperature 35°C DB/24WB; in heating mode: indoor temperature is 20°C DB, outdoor temperature is 7°C DB/6°CWB).

TECHNICAL DATA FOR THREE COMBINATIONS

MODEL		VVEA-1624R	VVEA-1680R	VVEA-1735R	VVEA-1790R	VVEA-1845R
COMBINATIONS		VVEA-504R	VVEA-560R	VVEA-560R	VVEA-560R	VVEA-615R
		7VF150015	7VF150016	7VF150016	7VF150016	7VF150017
		VVEA-560R	VVEA-560R	VVEA-560R	VVEA-615R	VVEA-615R
		7VF150016	7VF150016	7VF150016	7VF150017	7VF150017
		VVEA-560R	VVEA-560R	VVEA-615R	VVEA-615R	VVEA-615R
		7VF150016	7VF150016	7VF150017	7VF150017	7VF150017
Phase		<i>Three phases</i>				
Power	HP	58	60	62	64	66
COOLING MODE						
Rated power*	kW	162.40	168.00	173.50	179.00	184.50
Rated power input	kW	50.59	51.69	54.46	57.23	60.00
Max. power input	kW	92.50	96.00	97.00	98.00	99.00
Rated current	A	83.55	85.37	89.94	94.52	99.09
Max. current	A	152.76	158.54	160.20	161.85	163.50
EER		3.21	3.25	3.19	3.13	3.08
SEER		6.06	5.90	5.84	5.79	5.74
Seasonal operating limits		239	233	231	229	227
HEATING MODE						
Rated power*	kW	162.40	168.00	173.50	179.00	184.50
Rated power input	kW	45.25	47.33	49.46	51.60	53.73
Max. power input	kW	84.30	88.20	89.20	90.20	91.20
Rated current	A	74.73	78.16	81.68	85.21	88.74
Max. current	A	139.22	145.66	147.31	148.97	150.62
COP		3.59	3.55	3.51	3.47	3.43
SCOP		3.95	3.93	3.86	3.81	3.76
Seasonal operating limits		155	154	151	149	147
POWER SUPPLY						
Phase/Voltage/Frequency		3P/380-415V/50-60Hz				
PERFORMANCE						
Airflow (HS)	m ³ /h	55000	57000	57000	57000	57000
Sound pressure (HS)	dB(A)	68.00	68.00	68.00	68.50	69.00
INSTALLATION						
External dimensions (WxHxD)	mm	1410x1690x750 + 1410x1690x750 + 1410x1690x750				
Shipping dimensions (WxHxD)	mm	1515x1858x850 + 1515x1858x850 + 1515x1858x850				
Net weight/Gross weight	kg	366/395 + 375/404 + 375/404		375/404 + 375/404 + 375/404		
Compressor	Type	Scroll DCI				
	Brand	Mitsubishi Electric				
	Number of compressors	6				
Refrigerant		R410A				
Charge	kg	30				
Liquid pipe diameter	inches	3/4"				
Suction pipe diameter	inches	1"5/8				
Suction pipe diameter haut	inches	1"1/2				
Max. length	m	1000				
Max. length (equivalent/actual)	m	260/220				
Max. height between indoor and outdoor units (ODU down/up) (1)	m	110/90				
Standard height between indoor and outdoor units (ODU down/up) (2)	m	50/40				
Max. height between indoor units (3)	m	30				
Standard height between indoor units (4)	m	18				
External static pressure	Pa	110				
Indoor/outdoor unit power ratio (min./max.)	%	50-130				
Maximum number of connectable indoor units	quantity	64				
OPERATING LIMITS						
Cooling mode (min./max.)	°C	-5/-52				
Heating mode (min./max.)	°C	-27/-21				

(1) If the height difference between the outdoor and the indoor units is from 50 to 110m, you MUST contact your local distributor/dealer for individual design and production.

(2) Standard design and production in the factory.

(3) If the height difference between the indoor units is from 18 to 30m, you MUST contact your local distributor/dealer for individual design and production.

(4) Standard design and production in the factory.

* All the specifications are tested under nominal condition (in cooling mode: indoor temperature is 27°C DB/19°C WB, outdoor temperature 35°C DB/24WB; in heating mode: indoor temperature is 20°C DB, outdoor temperature is 7°C DB/6°CWB).

TECHNICAL DATA FOR FOUR COMBINATIONS

MODEL		VVEA-1908R	VVEA-1962R	VVEA-2016R	VVEA-2072R	VVEA-2128R	VVEA-2184R
COMBINATIONS	VVEA-450R	VVEA-450R	VVEA-504R	VVEA-504R	VVEA-504R	VVEA-504R	VVEA-504R
	7VF150014	7VF150014	7VF150015	7VF150015	7VF150015	7VF150015	7VF150015
	VVEA-450R	VVEA-504R	VVEA-504R	VVEA-504R	VVEA-504R	VVEA-504R	VVEA-560R
	7VF150014	7VF150015	7VF150015	7VF150015	7VF150015	7VF150015	7VF150016
	VVEA-504R	VVEA-504R	VVEA-504R	VVEA-504R	VVEA-504R	VVEA-560R	VVEA-560R
	7VF150015	7VF150015	7VF150015	7VF150015	7VF150015	7VF150016	7VF150016
	VVEA-504R	VVEA-504R	VVEA-504R	VVEA-560R	VVEA-560R	VVEA-560R	VVEA-560R
	7VF150015	7VF150015	7VF150015	7VF150016	7VF150016	7VF150016	7VF150016
Phase		Three phases					Three phases
Power	HP	68	70	72	74	76	78
COOLING MODE							
Rated power*	kW	190.80	196.20	201.60	207.20	212.80	218.40
Rated power input	kW	60.38	62.45	64.52	65.62	66.72	67.82
Max. power input	kW	107.20	110.60	114.00	117.50	121.00	124.50
Rated current	A	99.72	103.14	106.55	108.37	110.19	112.01
Max. current	A	177.04	182.66	188.27	194.05	199.83	205.61
EER		3.16	3.14	3.12	3.16	3.19	3.22
SEER		6.64	6.55	6.48	6.30	6.15	6.02
Seasonal operating limits		263	259	256	249	243	238
HEATING MODE							
Rated power*	kW	190.80	196.20	201.60	207.20	212.80	218.40
Rated power input	kW	50.18	52.49	54.79	56.87	58.95	61.02
Max. power input	kW	96.40	99.20	102.00	105.90	109.80	113.70
Rated current	A	82.88	86.68	90.49	93.92	97.35	100.78
Max. current	A	159.21	163.83	168.45	174.89	181.34	187.78
COP		3.80	3.74	3.68	3.64	3.61	3.58
SCOP		4.08	4.04	3.99	3.98	3.96	3.94
Seasonal operating limits		160	159	157	156	155	155
POWER SUPPLY							
Phase/Voltage/Frequency		3P/380-415V/50-60Hz					
PERFORMANCE							
Airflow (HS)	m ³ /h	68000	68000	68000	70000	72000	74000
Sound pressure (HS)	dB(A)	69.00	69.00	69.00	69.00	69.00	69.00
INSTALLATION							
External dimensions (WxHxD)	mm	1410x1690x750 + 1410x1690x750 + 1410x1690x750 + 1410x1690x750					
Shipping dimensions (WxHxD)	mm	1515x1858x850 + 1515x1858x850 + 1515x1858x850 + 1515x1858x850					
Net weight/Gross weight	kg	366/395 + 366/395 + 366/395 + 366/395			366/395 + 366/395 + 366/395 + 375/404	366/395 + 366/395 + 375/404 + 375/404	366/395 + 375/404 + 375/404 + 375/404
Compressor	Type	Scroll DCI					
	Brand	Mitsubishi Electric					
	Number of compressors	8					
Refrigerant							
Charge	kg	R410A					
Liquid pipe diameter	inches	40					
Suction pipe diameter	inches	7/8"					
Suction pipe diameter haut	inches	1"3/4					
Max. length	m	1"5/8					
Max. length (equivalent/actual)	m	1000					
Max. height between indoor and outdoor units (ODU down/up) (1)	m	260/220					
Standard height between indoor and outdoor units (ODU down/up) (2)	m	110/90					
Max. height between indoor units (3)	m	50/40					
Standard height between indoor units (4)	m	30					
External static pressure	Pa	18					
Indoor/outdoor unit power ratio (min./max.)	%	110					
Maximum number of connectable indoor units	quantity	50-130					
OPERATING LIMITS							
Cooling mode (min./max.)	°C	-5-52					
Heating mode (min./max.)	°C	-27-21					

(1) If the height difference between the outdoor and the indoor units is from 50 to 110m, you MUST contact your local distributor/dealer for individual design and production.

(2) Standard design and production in the factory.

(3) If the height difference between the indoor units is from 18 to 30m, you MUST contact your local distributor/dealer for individual design and production.

(4) Standard design and production in the factory.

* All the specifications are tested under nominal condition (in cooling mode: indoor temperature is 27°C DB/19°C WB, outdoor temperature 35°C DB/24WB; in heating mode: indoor temperature is 20°C DB, outdoor temperature is 7°C DB/6°CWB).

TECHNICAL DATA FOR FOUR COMBINATIONS

MODEL		VVEA-2240R	VVEA-2295R	VVEA-2350R	VVEA-2405R	VVEA-2460R
COMBINATIONS		VVEA-560R	VVEA-560R	VVEA-560R	VVEA-560R	VVEA-615R
		7VF150016	7VF150016	7VF150016	7VF150016	7VF150017
		VVEA-560R	VVEA-560R	VVEA-560R	VVEA-615R	VVEA-615R
		7VF150016	7VF150016	7VF150016	7VF150017	7VF150017
		VVEA-560R	VVEA-560R	VVEA-615R	VVEA-615R	VVEA-615R
		7VF150016	7VF150016	7VF150017	7VF150017	7VF150017
		VVEA-560R	VVEA-615R	VVEA-615R	VVEA-615R	VVEA-615R
		7VF150016	7VF150017	7VF150017	7VF150017	7VF150017
Phase		<i>Three phases</i>				
Power	HP	80	82	84	86	88
COOLING MODE						
Rated power*	kW	224.00	229.50	235.00	240.50	246.00
Rated power input	kW	68.92	71.69	74.46	77.23	80.00
Max. power input	kW	128.00	129.00	130.00	131.00	132.00
Rated current	A	113.83	118.40	122.97	127.55	132.12
Max. current	A	211.39	213.04	214.70	216.35	218.00
EER		3.25	3.20	3.16	3.11	3.08
SEER		5.90	5.86	5.81	5.77	5.74
Seasonal operating limits		233	231	229	228	227
HEATING MODE						
Rated power*	kW	224.00	229.50	235.00	240.50	246.00
Rated power input	kW	63.10	65.24	67.37	69.51	71.64
Max. power input	kW	117.60	118.60	119.60	120.60	121.60
Rated current	A	104.21	107.74	111.26	114.79	118.31
Max. current	A	194.22	195.87	197.52	199.17	200.82
COP		3.55	3.52	3.49	3.46	3.43
SCOP		3.93	3.88	3.83	3.79	3.76
Seasonal operating limits		154	152	150	149	147
POWER SUPPLY						
Phase/Voltage/Frequency		3P/380-415V/50-60Hz				
PERFORMANCE						
Airflow (HS)	m ³ /h	76000	76000	76000	76000	76000
Sound pressure (HS)	dB(A)	69.00	69.00	69.50	70.00	70.00
INSTALLATION						
External dimensions (WxHxD)	mm	1410x1690x750 + 1410x1690x750 + 1410x1690x750 + 1410x1690x750				
Shipping dimensions (WxHxD)	mm	1515x1858x850 + 1515x1858x850 + 1515x1858x850 + 1515x1858x850				
Net weight/Gross weight	kg	375/404 + 375/404 + 375/404 + 375/404				
Type		Scroll DCI				
Compressor Brand		Mitsubishi Electric				
Number of compressors		8				
Refrigerant		R410A				
Charge	kg	40				
Liquid pipe diameter	inches	7/8"			1"	
Suction pipe diameter	inches	1 3/4			2"	
Suction pipe diameter haut	inches	1 5/8			1 3/4	
Max. length	m	1000				
Max. length (equivalent/actual)	m	260/220				
Max. height between indoor and outdoor units (ODU down/up) (1)	m	110/90				
Standard height between indoor and outdoor units (ODU down/up) (2)	m	50/40				
Max. height between indoor units (3)	m	30				
Standard height between indoor units (4)	m	18				
External static pressure	Pa	110				
Indoor/outdoor unit power ratio (min./max.)	%	50-130				
Maximum number of connectable indoor units	quantity	64				
OPERATING LIMITS						
Cooling mode (min./max.)	°C	-5~-52				
Heating mode (min./max.)	°C	-27~-21				

(1) If the height difference between the outdoor and the indoor units is from 50 to 110m, you MUST contact your local distributor/dealer for individual design and production.

(2) Standard design and production in the factory.

(3) If the height difference between the indoor units is from 18 to 30m, you MUST contact your local distributor/dealer for individual design and production.

(4) Standard design and production in the factory.

* All the specifications are tested under nominal condition (in cooling mode: indoor temperature is 27°C DB/19°C WB, outdoor temperature 35°C DB/24WB; in heating mode: indoor temperature is 20°C DB, outdoor temperature is 7°C DB/6°CWB).



VRF
Water condensing

FlowLogic **V**

COMPATIBLE



+ PRODUCT

- Water condensation
- Co-axial heat exchangers
- Compact design
- Quiet



RWV06
(optional, see
configuration
page 58)



RWV09
(optional, see
configuration
page 59)

FEATURES

TECHNOLOGY



DC INVERTER

INSTALLER FUNCTIONS



SELF DIAGNOSTIC



BMS COMPATIBLE



SERVICE MONITOR
TOOL

WATER FLOWLOGIC

VRF Water condensing



THE + « SUSTAINABLE DEVELOPMENT »

- > High energy efficiency (COP > 6).
- > Energy recovery from water loops.

THE + « USER »

- > 100% indoor application.
- > Practical and discreet solution.

THE + « INSTALLER »

- > Stacked installation is possible.
- > Up to 300 m of refrigeration network and 50 m height difference.

THE + « TECHNOLOGY »

- > Up to 19 indoor units.
- > Outside temperature does not affect performance.
- > Airconnect Pro: remote maintenance and management option.

ACCESSORIES

ACCESSORY	PART NUMBER	REF.	PHOTO	FUNCTION	COMMENT
Gather pipe kit for 2 outdoor groups	7ACFHH013	TBS20		• Refrigerant gathering	• For 2 outdoor groups
Gather pipe kit for 3 outdoor groups	7ACFHH014	TBS30		• Refrigerant gathering	• For 3 outdoor groups
Gather pipe kit for 4 outdoor groups	7ACFHH014 + 7ACFHH015	TBS30 + TAU2040		• Refrigerant gathering	• For 4 outdoor groups
Manifold pipe (gas + liquid)	7ACFHH001	TAU335		• Refrigerant gathering	• 33,5 kW > Total IDU power
	7ACFHH002	TAU506		• Refrigerant gathering	• 33,5 kW ≤ Total IDU power < 50,6 kW
	7ACFHH003	TAU730		• Refrigerant gathering	• 50,6 kW ≤ Total IDU power < 73 kW
	7ACFHH004	TAU1350		• Refrigerant gathering	• 73 kW ≤ Total IDU power < 135 kW
	7ACFHH005	TAU2040		• Refrigerant gathering	• 135 kW ≤ Total IDU power
Maintenance tool	7ACELH014	TD02		• Working parameters monitoring and recording tool	
Smart WiFi module	7ACEL1869	-		• Remote control by the smart WiFi module and controlled by the AirConnect Smart application	• Module dimensions: 86x86x12 mm.

TECHNICAL DATA

OUTDOOR UNIT	YWC220-H13	YWC280-H13	YWC335-H13
Part number	7SP14H038	7SP14H039	7SP14H040

POWER

Capacity range	HP	8	10	12
Cooling	kW	22.4	28	33.5
Heating	kW	25	31.5	37.5

ELECTRICAL PARAMETERS

Phase/Voltage/Frequency			3P/380-400V/50-60Hz	3P/380-400V/50-60Hz	3P/380-400V/50-60Hz
Cooling	Rated power input	kW	4.50	6.00	7.70
	Max. power input	kW	13.00	15.00	17.00
	Rated current	A	7.20	9.60	12.32
	Max. current	A	20.79	23.99	27.19
Heating	Rated power input	kW	4.15	5.80	7.80
	Max. power input	kW	13.00	15.00	17.00
	Rated current	A	6.64	9.28	12.47
	Max. current	A	20.79	23.99	27.19
EER			4.98	4.67	4.35
COP			6.02	5.43	4.81

PERFORMANCE

Water flow (HS)	m ³ /h	4.8	6	7.2
Sound pressure level (HS)	dB(A)	50	51	53
Sound power level (HS)	dB(A)	61	62	64

INSTALLATION

External dimensions (WxHxD)	mm	775x995x545	775x995x545	775x995x545
Shipping dimensions (WxHxD)	mm	875x1182x655	875x1182x655	875x1182x655
Net weight/Gross weight	kg	172/183	172/183	172/183
Compressor type		Scroll DCI	Scroll DCI	Scroll DCI
Refrigerant/GWP		R410A/2088	R410A/2088	R410A/2088
Refrigerant charge	kg	2	2	2
Liquid pipe diameter	mm	3/8"	3/8"	1/2"
Suction pipe diameter	mm	3/4"	7/8"	1"
Oil equalization pipe	mm	3/8"	3/8"	3/8"
Total pipe length	m	300	300	300
Max. pipe length (equivalent/actual)	m	150/120	150/120	150/120
Max. height between indoor and outdoor units* (ODU up/down)	m	50/40	50/40	50/40

WATER SIDE

Inlet water connection pipe	mm	DN32	DN32	DN32
Outlet water connection pipe	mm	DN32	DN32	DN32
Pressure drop (inlet and outlet)	Kpa	35	50	70
Connection type		inner grooved	inner grooved	inner grooved
Max. system water pressure	Mpa	1.6	1.6	1.6
Inlet water temperature range (cooling/heating)	°C	7°/45°	7°/45°	7°/45°

CONNECTION RATIO

Connectable indoor unit ratio	%	50-130	50-130	50-130
Maximum number of indoor units		13	16	19

The indoor units of the VRF range adapt to all destinations and all projects. From the 4-way cassette to the 360° cassette, from the extra-flat duct to the high-pressure duct and from the wall to the ceiling-light, Airwell meets all the needs in terms of thermal comfort.

- ▶ Fitted with DC inverter fan motors offering high aerodynamic performance with a very low sound level and an electronic expansion valve offering 475 opening steps, the indoor units in the range will combine **comfort and performance**.
- ▶ The entire range of indoor units offers a **standard dry contact** allowing the unit to be controlled through a window or door contact or a «room card» for a hotel application.
- ▶ At Airwell, each indoor unit is delivered with its RWV05 wired or RCV03 infrared remote control.

INDOOR UNIT MODELS

REFRIGERANT TYPE

p.40		HIGH WALL	HVVA		R410A
p.41		CASSETTE 600X600	CVQA		R410A
p.42		1-WAY CASSETTE	CVPA		R410A
p.43		2-WAYS CASSETTE	CVOA		R410A
p.44		CASSETTE 360°	CVTA		R410A
p.45		FLOOR CEILING	FVVA		R410A
p.46		DUCTED LOW STATIC PRESSURE	DVLA		R410A
p.47		DUCTED MEDIUM STATIC PRESSURE	DVMA		R410A
p.48		DUCTED HIGH STATIC PRESSURE	DVHA		R410A
p.49		FULL FRESH AIR UNIT	DVFA		R410A
p.50		CONSOLE	XVVA		R410A
p.52		AHU CONNECTION KIT			



CAPACITY (KBTU/H)	5	7	9	12	16	18	24	28	30	38	48	60	72	96	192	
CAPACITY (HP)	0.5	0.75	1.25	1.5	1.75	2.25	3	3.5	3.75	4.75	6	7	9	12	24	
COOLING MODE (KW)	1.5	2.2	2.8	3.6	4.5	5.6	7.1	8	9	11.2	14	16	22.6	28	56	
HEATING MODE (KW)	1.7	2.5	3.2	4	5	6.3	8	9	10	12.5	16	18	25	31.5	63	73.5

HVVA		•	•	•	•	•	•			•						
CVQA	•	•	•	•	•	•										
CVPA		•	•	•												
CVOA		•	•	•	•	•										
CVTA		•	•	•	•	•	•			•	•	•	•			
FVVA			•	•	•	•	•	•	•	•	•	•				
DVLA		•	•	•	•											
DVMA	•	•	•	•			•	•	•	•	•	•				
DVHA													•	•		
DVFA							•	•		•	•	•	•	•		
XVVA			•	•			•									
AHU connection kit			•	•	•	•	•	•	•	•	•	•	•	•	•	•



VRF
Indoor units

HVVA High wall



RCV03
included

+ PRODUCT

- RCV03 remote control included (see page 60)
- DC Inverter tangential fan
- Panel digital screen
- Dry contact available



RWV05
(optional, see
configuration
page 61)



RWV03
(optional)

FEATURES

TECHNOLOGY



ELECTRONIC
EXPANSION VALVE

FUNCTIONS USERS



I FEEL



PROGRAMMABLE
TIMER



AUTO RESTART
(MEMORY)

INSTALLER FUNCTIONS



ERROR CODE VIA
INDOOR UNIT



DRY CONTACT
ON/OFF

THE + «SUSTAINABLE DEVELOPMENT»

- > Energy savings (mode locking, setpoint limits).

THE + «USER»

- > Simple and elegant design.
- > Silent operation.
- > Multiple applications can be connected using the dry contact: room card, presence detector.

THE + «INSTALLER»

- > Slim design.

THE + «TECHNOLOGY»

- > Optimal regulation thanks to its electronic expansion valve.

TECHNICAL DATA

INDOOR UNIT		HVVA-025/022N-01M22	HVVA-035N-01M22	HVVA-050/045N-01M22	HVVA-070N-01M22	HVVA-090N-01M22		
Part number		7VF020001	7VF020002	7VF020003	7VF020004	7VF020005		
Phase		Single phase						
RATED POWER								
Cooling mode	kBtu/h	7.50	9.50	12.30	15.30	19.10	24.20	30.70
	kW	2.20	2.80	3.60	4.50	5.60	7.10	9.00
Heating mode	kBtu/h	8.50	10.90	13.60	17.10	21.50	27.30	34.10
	kW	2.50	3.20	4.00	5.00	6.30	8.00	10.00
ELECTRICAL PARAMETERS								
Phase/Voltage/Frequency		1P/220-240V/50-60Hz						
PERFORMANCES								
Airflow (LS/MS/HS)	m³/h	420/480/550	470/530/600	500/560/630	650/720/800	720/800/920	800/920/1010	1400/1500/1600
Sound pressure (LS/MS/HS)	dB(A)	29/31/35	29/31/36	29/33/37	34/36/39	35/39/40	36/40/44	41/44/49
Sound power level (LS/MS/HS)	dB(A)	42/47/50	44/48/52	50/51/54	51/53/56	52/54/57	54/56/58	54/58/61
INSTALLATION								
External dimensions (WxHxD)	mm	855x280x208	855x280x208	1115x336x243	1115x336x243	1316x365x270		
Shipping dimensions (WxHxD)	mm	954x355x279	954x355x279	1206x418x342	1206x418x342	1403x463x384		
Net weight/Gross weight	kg	9.9/12	9.9/12	15.8/18.9	15.8/18.9	21.8/26.3		
Liquid pipe diameter	inches	1/4"	1/4"	1/4"	3/8"	3/8"		
Suction pipe diameter	inches	3/8"	1/2"	1/2"	5/8"	5/8"		

CVQA

Cassette 600x600



RWV05 included

VRF
Indoor units



THE + « SUSTAINABLE DEVELOPMENT »

- > Energy savings (mode locking, setpoint limits).

THE + « USER »

- > Air renewal by supply of fresh air.
- > Multiple applications can be connected using the dry contact: room card, presence detector.

THE + « INSTALLER »

- > Easy integration into false ceilings thanks to its reduced height.
- > Simple installation thanks to its integrated condensates pump.

THE + « TECHNOLOGY »

- > Optimal regulation thanks to its electronic expansion valve.
- > Individual opening of each flap.

TECHNICAL DATA

INDOOR UNIT		CVQA-025/022/015N-01M22			CVQA-050/045/035N-01M22		
Part number		7VF040001			7VF040002		
Phase		Single phase					
RATED POWER							
Cooling mode	kBtu/h	5.10	7.50	9.50	12.30	15.30	19.10
	kW	1.50	2.20	2.80	3.60	4.50	5.60
Heating mode	kBtu/h	5.80	8.50	10.90	13.60	17.10	21.50
	kW	1.70	2.50	3.20	4.00	5.00	6.30
ELECTRICAL PARAMETERS							
Phase/Voltage/Frequency		1P/220-240V/50-60Hz					
PERFORMANCES							
Airflow (LS/MS/HS)	m³/h	400/450/520		400/450/520	450/520/650	520/650/760	
Sound pressure (LS/MS/HS)	dB(A)	29/30/32		29/30/33		30/32/34	
Sound power level (LS/MS/HS)	dB(A)	43/44/46		43/44/47		44/46/48	
INSTALLATION							
External dimensions (WxHxD)	mm	570x260x570					
Shipping dimensions (WxHxD)	mm	718x380x680					
Net weight/Gross weight	kg	16/19			19/22		
Liquid pipe diameter	inches	1/4"			1/4"		
Suction pipe diameter	inches	3/8"			1/2"		
PANEL							
Panel part number		7ACVF0601					
External dimensions (WxHxD)	mm	620x60x620					
Shipping dimensions (WxHxD)	mm	660x115x660					

+ PRODUCT

- RWV05 remote control included (see page 61)
- New design
- New DC Inverter fan motor
- Integrated condensates pump
- Fresh air inlet
- Dry contact available



RCV03 (optional)



RWV03 (optional)

FEATURES

TECHNOLOGY



ELECTRONIC EXPANSION VALVE

AIR QUALITY / CLEAN



FRESH AIR

FUNCTIONS USERS



I FEEL



PROGRAMMABLE TIMER



AUTO RESTART (MEMORY)

INSTALLER FUNCTIONS



INTEGRATED CONDENSATES PUMP



DRY CONTACT ON/OFF



DRV
Indoor units

CVPA 1-way cassette



RWV05
included



+ PRODUCT

- RWV05 remote control included (see page 61)
- Contemporary design
- Integrated condensate pump
- Low noise level



RCV03
(optional)



RWV03
(optional)



RWV07
(optional)

FEATURES

TECHNOLOGY



ELECTRONIC
EXPANSION VALVE

USER FUNCTIONS



I FEEL



PROGRAMMABLE
TIMER



AUTO RESTART
(MEMORY)

INSTALLER FUNCTIONS



INTEGRATED
CONDENSATES
PUMP



DRY CONTACT
ON/OFF

+ «SUSTAINABLE DEVELOPMENT»

- > Energy savings (mode blocking, setpoint limiting).

+ «INSTALLER»

- > Easy integration in false ceilings, thanks to its low thickness.
- > Easy installation, thanks to its integrated condensate pump.

+ «TECHNOLOGY»

- > Optimal regulation, thanks to its electronic expansion valve.

TECHNICAL DATA

INDOOR UNIT		CVPA-025/022N-01M22	CVPA-035N-01M22	
Part number		7VF040004	7VF040003	
Phase		Single phase		
RATED POWER				
Cooling mode	kBtu/h	7.50	9.60	12.30
	kW	2.20	2.80	3.60
Heating mode	kBtu/h	8.50	10.90	13.60
	kW	2.50	3.20	4.00
ELECTRICAL PARAMETERS				
Phase/Voltage/Frequency		1P/220-240V/50-60Hz		
PERFORMANCES				
Airflow (LS/MS/HS)	m ³ /h	450/490/530	490/530/550	
Sound pressure (LS/MS/HS)	dB(A)	24/29/32	25/30/34	
Sound power level (LS/MS/HS)	dB(A)	38/43/46	39/44/48	
INSTALLATION				
External dimensions (WxHxD)	mm	875x185x505		
Shipping dimensions (WxHxD)	mm	1028x270x581		
Net weight/Gross weight	kg	15.3/17.9		
Liquid pipe diameter	inches	1/4"		
Suction pipe diameter	inches	3/8"	1/2"	
PANEL				
Panel part number		7ACVFH004		
External dimensions (WxHxD)	mm	1050x122x560		
Shipping dimensions (WxHxD)	mm	1133x197x623		
Net weight/Gross weight	kg	5.3/8.3		

CVOA

2-ways cassette



RWV05
included

DRV
Indoor units



⊕ «SUSTAINABLE DEVELOPMENT»

> Energy savings (mode blocking, setpoint limiting).

⊕ «INSTALLER»

> Easy integration in false ceilings, thanks to its low thickness.
> Easy installation, thanks to its integrated condensate pump.

⊕ «TECHNOLOGY»

> Optimal regulation, thanks to its electronic expansion valve.

+ PRODUCT

- RWV05 remote control included (see page 61)
- Contemporary design
- Integrated condensate pump
- Low noise level



RCV03
(optional)



RWV03
(optional)



RWV07
(optional)

TECHNICAL DATA

INDOOR UNIT		CVOA-025N-01M22	CVOA-035N-01M22	CVOA-050/040-01M22	
Part number		7VF040005	7VF040006	7VF040007	
Phase		Single phase			
RATED POWER					
Cooling mode	kBtu/h	9.60	12.30	15.40	19.10
	kW	2.80	3.60	4.50	5.60
Heating mode	kBtu/h	10.90	13.60	17.10	21.50
	kW	3.20	4.00	5.00	6.30
ELECTRICAL PARAMETERS					
Phase/Voltage/Frequency		1P/220-240V/50-60Hz			
PERFORMANCES					
Airflow (LS/MS/HS)	m³/h	550/700/840	550/700/840	550/700/840	
Sound pressure (LS/MS/HS)	dB(A)	33/37/42	33/37/42	34/39/44	
Sound power level (LS/MS/HS)	dB(A)	46/50/55	46/50/55	47/52/57	
INSTALLATION					
External dimensions (WxHxD)	mm	817x220x620			
Shipping dimensions (WxHxD)	mm	1015x260x6950			
Net weight/Gross weight	kg	21/23			
Liquid pipe diameter	inches	1/4"			
Suction pipe diameter	inches	3/8"	1/2"	1/2"	
PANEL					
Panel part number		7ACVFH005			
External dimensions (WxHxD)	mm	1055x68x680			
Shipping dimensions (WxHxD)	mm	1110x160x720			
Net weight/Gross weight	kg	7/8			

FEATURES

TECHNOLOGY



ELECTRONIC EXPANSION VALVE

USER FUNCTIONS



I FEEL



PROGRAMMABLE TIMER



AUTO RESTART (MEMORY)

INSTALLER FUNCTIONS



INTEGRATED CONDENSATES PUMP



DRY CONTACT ON/OFF



VRF
Indoor units

CVTA Cassette 360°



RWV05
included

+ PRODUCT

- RWV05 remote control included (see page 61)
- 360° air blowing
- New DC Inverter fan motor
- Integrated condensates pump
- Extra-slim cassette
- Fresh air inlet
- Dry contact available



RCV03
(optional)



RWV03
(optional)



RWV07
(optional)

FEATURES

TECHNOLOGY



ELECTRONIC
EXPANSION VALVE



MULTIFLOW 360°

AIR QUALITY / CLEAN



FRESH AIR

FUNCTIONS USERS



I FEEL



PROGRAMMABLE
TIMER



AUTO RESTART
(MEMORY)

INSTALLER FUNCTIONS



INTEGRATED
CONDENSATES
PUMP



DRY CONTACT
ON/OFF

THE + « SUSTAINABLE DEVELOPMENT »

- > Energy savings (mode locking, setpoint limits).

THE + « USER »

- > Optimal comfort with its 360° blown air output.
- > Air renewal by supply of fresh air.
- > Multiple applications can be connected using the dry contact: room card, presence detector.

THE + « INSTALLER »

- > Simple installation (180 mm high).

THE + « TECHNOLOGY »

- > Optimal regulation thanks to its electronic expansion valve.
- > Individual opening of each flap.

TECHNICAL DATA

INDOOR UNIT		CVTA-025/022N-01M22	CVTA-035N-01M22	CVTA-050/045N-01M22	CVTA-070N-01M22	CVTA-110/090N-01M22	CVTA-160/140N-01M22				
Part number		7VF040008	7VF040009	7VF040010	7VF040011	7VF040012	7VF040013				
Phase		Single phase									
RATED POWER											
Cooling mode	kBtu/h	7.50	9.50	12.30	15.30	19.10	24.20	30.70	38.20	47.70	54.60
	kW	2.20	2.80	3.60	4.50	5.60	7.10	9.00	11.20	14.00	16.00
Heating mode	kBtu/h	8.50	10.90	13.60	17.10	21.50	27.30	34.10	42.60	54.60	61.20
	kW	2.50	3.20	4.00	5.00	6.30	8.00	10.00	12.50	16.00	18.00
ELECTRICAL PARAMETERS											
Phase/Voltage/Frequency		1P/220-230V/50-60Hz									
PERFORMANCES											
Airflow (LS/MS/HS)	m³/h	620/810/1000	620/810/1000	620/810/1000	1000/1190/1380	1670/1860/2050	1720/1910/2100				
Sound pressure (LS/MS/HS)	dB(A)	25/27/30	25/27/30	27/29/32	29/30/33	31/34/35	31/35/37	36/40/44			
INSTALLATION											
External dimensions (WxHxD)	mm	840x183x840	840x183x840	840x183x840	840x204x840	840x204x840	840x288x840				
Shipping dimensions (WxHxD)	mm	983x268x983	983x268x983	983x268x983	983x290x983	983x331x983	983x373x983				
Net weight/Gross weight	kg	25/28	25/28	25/28	27/30	31/36	33/38				
Liquid pipe diameter	inches	1/4"	1/4"	1/4"	3/8"	3/8"	3/8"				
Suction pipe diameter	inches	3/8"	1/2"	1/2"	5/8"	5/8"	5/8"				
PANEL											
Panel part number		7ACVH003									
External dimensions (WxHxD)	mm	950x50x950									
Shipping dimensions (WxHxD)	mm	1013x123x1025									
Net weight/Gross weight	kg	6.5/9									

FVVA

Floor ceiling



RWV05
included

VRF
Indoor units



THE + « SUSTAINABLE DEVELOPMENT »

> Energy savings (mode locking, setpoint limits).

THE + « USER »

> Air blowing distance up to 11m.
> Horizontal and vertical airflow swing.
> Multiple applications can be connected using the dry contact: room card, presence detector.

THE + « INSTALLER »

> Horizontal or vertical installation.

THE + « TECHNOLOGY »

> Optimal regulation thanks to its electronic expansion valve.
> New centrifugal fan, acoustic reduction.

TECHNICAL DATA

INDOOR UNIT		FVVA-025N-01M22	FVVA-050/045/035N-01M22	FVVA-090/080/070N-01M22	FVVA-140/110N-01M22					
Part number		7VF010001	7VF010002	7VF010003	7VF010004					
Phase		Single phase								
RATED POWER										
Cooling mode	kBtu/h	9.50	12.28	15.35	19.11	24.23	27.30	30.71	38.21	48.00
	kW	2.80	3.60	4.50	5.60	7.10	8.00	9.00	11.20	14.00
Heating mode	kBtu/h	10.92	13.65	17.06	21.50	27.30	30.71	34.12	42.60	55.00
	kW	3.20	4.00	5.00	6.30	8.00	9.00	10.00	12.50	16.00
ELECTRICAL PARAMETERS										
Phase/Voltage/ Frequency		1P/220-230V/50-60Hz								
PERFORMANCES										
Airflow (LS/MS/HS)	m ³ /h	690/ 750/ 820	690/ 750/ 820	690/820/950	1240/ 1270/ 1420	1240/1420/1570	1750/1990/2110			
Sound pressure (LS/MS/HS)	dB(A)	34/36/ 38	34/36/ 38	35/38/42	41/44/ 46	41/44/47	43/46/50			
Sound power level (LS/MS/HS)	dB(A)	47/50/ 52	47/50/ 52	48/51/55	54/58/ 60	54/58/61	57/60/63			
INSTALLATION										
External dimensions (WxHxD)	mm	1000 x680 x230	1000x680x230	1325x680x230	1650x680x230					
Shipping dimensions (WxHxD)	mm	779 x1100 x305	1100x779x305	1425x779x305	1750x779x305					
Net weight/Gross weight	kg	27.9/ 33.6	27.9/33.6	35.8/42.1	43.5/50.5					
Liquid pipe diameter	inches	1/4"	1/4"	3/8"	3/8"					
Suction pipe diameter	inches	3/8"	1/2"	5/8"	5/8"					

+ PRODUCT

- RWV05 remote control included (see page 61)
- New DC Inverter fan motor
- New aesthetic and modern design
- New deflectors for better air distribution
- High airflow rate
- Improved component accessibility
- Dry contact available



RCV03
(optional)

RWV03
(optional)

FEATURES

TECHNOLOGY



ELECTRONIC
EXPANSION VALVE

FUNCTIONS USERS



I FEEL



PROGRAMMABLE
TIMER



AUTO RESTART
(MEMORY)

INSTALLER FUNCTIONS



DRY CONTACT
ON/OFF



VRF
Indoor units

DVLA Ducted low static pressure



RWV05
included

+ PRODUCT

- RWV05 remote control included (see page 61)
- New DC Inverter fan motor
- Integrated condensates pump
- Extra-slim unit
- Fresh air supply
- Adjustable static pressure 0-30 Pa
- Dry contact available



RCV03
(optional)



RWV03
(optional)

FEATURES

TECHNOLOGY



ELECTRONIC
EXPANSION VALVE



AIRFLOW 4D

AIR QUALITY / CLEAN



FRESH AIR

FUNCTIONS USERS



I FEEL



SUPER
QUIET



PROGRAMMABLE
TIMER



AUTO RESTART
(MEMORY)

INSTALLER FUNCTIONS



INTEGRATED
CONDENSATES
PUMP



DRY CONTACT
ON/OFF

THE + « SUSTAINABLE DEVELOPMENT »

- > Energy savings (mode locking, setpoint limits).

THE + « USER »

- > Super quiet 21 dB.
- > Design solution thanks to its motorised panel.
- > Directable airflow.
- > Air renewal by supply of fresh air.
- > Multiple applications can be connected using the dry contact: room card, presence detector.

THE + « INSTALLER »

- > Simple installation: similar dimensions across the range.
- > Slim design 185 mm.

THE + « TECHNOLOGY »

- > Optimal regulation thanks to its electronic expansion valve.
- > Front panel with digital display.

TECHNICAL DATA

INDOOR UNIT		DVLA-025/022-01M22	DVLA-035-01M22	DVLA-045-01M22
Part number		7VF030003	7VF030004	7VF030005
Phase		Single phase		
RATED POWER				
Cooling mode	kBtu/h	7.50	9.50	12.30
	kW	2.20	2.80	3.60
Heating mode	kBtu/h	8.50	10.90	13.60
	kW	2.50	3.20	4.00
ELECTRICAL PARAMETERS				
Phase/Voltage/Frequency		1P/220-230V/50-60Hz		
PERFORMANCES				
Airflow (LS/MS/HS)	m³/h	360/420/480	370/430/550	460/540/600
Sound pressure (LS/MS/HS)	dB(A)	20/23/27	24/27/30	26/29/32
Sound power level (LS/MS/HS)	dB(A)	34/37/41	38/41/44	40/43/46
INSTALLATION				
External dimensions (WxHxD)	mm	850x185x420	850x185x420	850x185x420
Shipping dimensions (WxHxD)	mm	1045x270x540	1045x270x540	1045x270x540
Net weight/Gross weight	kg	17.5/22.5	17.5/22.5	18.5/23.5
Liquid pipe diameter	inches	1/4"		
Suction pipe diameter	inches	3/8"	1/2"	
External static pressure (min./standard/max.)	Pa	0/15/30		
PANEL				
Panel part number		7ACVF0587		
Dimensions (WxHxD)	Supply	mm	890x100x190	
	Return	mm	890x291x32.4	
Shipping dimensions (WxHxD)	mm	938x335x220		
Net weight/Gross weight	kg	4/5		

DVMA Ducted medium static pressure



RWV05 included

VRF Indoor units



THE + « SUSTAINABLE DEVELOPMENT »

> Energy savings (mode locking, setpoint limits).

THE + « USER »

> Air renewal by supply of fresh air.
> Multiple applications can be connected using the dry contact: room card, presence detector.

THE + « INSTALLER »

> Ease of installation thanks to its small dimensions.
> Integrated condensates pump.

THE + « TECHNOLOGY »

> Optimal regulation thanks to its electronic expansion valve.
> Adaptability to the ventilation network thanks to its adjustable static pressure.

+ PRODUCT

- RWV05 remote control included (see page 61)
- New motoventilateur DC Inverter
- Integrated condensates pump
- Wide power range
- Extra-slim unit 250 mm
- Adjustable static pressure from 20 to 200 Pa
- Dry contact available



RCV03 (optional)

RWV03 (optional)

TECHNICAL DATA

INDOOR UNIT	DVMA-025/022/015N-01M22	DVMA-035N-01M22	DVMA-045N-01M22	DVMA-080/070/050N-01M22	DVMA-090N-01M22	DVMA-110N-01M22	DVMA-160/140N-01M22						
Part number	7VF030010	7VF030011	7VF030012	7VF030013	7VF030014	7VF030015	7VF030016						
Phase	Single phase												
RATED POWER													
Power	HP	0.50	0.80	1.00	1.25	1.70	2.00	2.50	3.00	3.20	4.00	5.00	6.00
Cooling mode	kBtu/h	5.10	7.50	9.60	12.30	15.30	19.10	24.20	27.30	30.70	38.20	47.80	54.60
	kW	1.50	2.20	2.80	3.60	4.50	5.60	7.10	8.00	9.00	11.20	14.00	16.00
Heating mode	kBtu/h	5.80	8.50	10.90	13.70	17.00	21.50	27.30	30.70	34.10	44.40	55.60	61.40
	kW	1.70	2.50	3.20	4.00	5.00	6.30	8.00	9.00	10.00	13.00	16.30	18.00
ELECTRICAL PARAMETERS													
Phase/Voltage/Frequency	1P/220-240V/50-60Hz												
PERFORMANCES													
Airflow (LS/MS/HS)	m³/h	390/440/515	390/470/545	420/498/570	550/625/700	640/765/915	875/1050/1275	1000/1200/1450	1400/1700/2000	1400/1750/2150	1600/1950/2350		
Sound pressure (LS/MS/HS)	dB(A)	25/27/29	25/28/30	27/29/31	28/30/32	29/31/33	29/31/34	30/33/35	30/33/36	32/35/38	32/36/40	34/38/42	
		37/39/41	37/40/42	39/41/43	40/42/44	41/43/45	41/43/46	42/45/47	42/45/48	44/47/50	44/47/52	46/50/54	
Sound power level (LS/MS/HS)	dB(A)	37/39/41	37/40/42	39/41/43	40/42/44	41/43/45	41/43/46	42/45/47	42/45/48	44/47/50	44/47/52	46/50/54	
INSTALLATION													
External dimensions (WxHxD)	mm	700x248x700			1100x248x700			1500x248x700					
Shipping dimensions (WxHxD)	mm	932x280x835			1332x280x835			1698x305x857					
Net weight/Gross weight	kg	27/32		28.5/33.5	36.8/43.4		39.4/45.4	48.3/56.5	51.3/59.5				
Liquid pipe diameter	inches	1/4"						3/8"					
Suction pipe diameter	inches	3/8"		1/2"					5/8"				
External static pressure (standard/max.)	Pa	20/200						20/180					

FEATURES

TECHNOLOGY



ELECTRONIC EXPANSION VALVE

AIR QUALITY / CLEAN



FRESH AIR

FUNCTIONS USERS



I FEEL



SUPER QUIET



PROGRAMMABLE TIMER



AUTO RESTART (MEMORY)

INSTALLER FUNCTIONS



INTEGRATED CONDENSATES PUMP



DRY CONTACT ON/OFF



VRF
Indoor units

DVHA

Ducted high static pressure



RWV05
included

+ PRODUCT

- RWV05 remote control included (see page 61)
- High static pressure and airflow 4050 m³/h
- High power from 5.6 to 28 kW
- Dry contact available



RCV03
(optional)



RWV03
(optional)

FEATURES

TECHNOLOGY



ELECTRONIC
EXPANSION VALVE

FUNCTIONS USERS



I FEEL



PROGRAMMABLE
TIMER



AUTO RESTART
(MEMORY)

INSTALLER FUNCTIONS



DRY CONTACT
ON/OFF

THE + « SUSTAINABLE DEVELOPMENT »

- > Energy savings (mode locking, setpoint limits).

THE + « USER »

- > Static pressure up to 196 Pa to adapt to any type of ventilation network.

THE + « INSTALLER »

- > Possible installation on textile duct.

THE + « TECHNOLOGY »

- > Optimal regulation thanks to its electronic expansion valve.
- > Adaptability to the ventilation network thanks to its adjustable static pressure.

TECHNICAL DATA

INDOOR UNIT		DVHA-280/220N-01M22	
Part number		7VF030006	
Phase		Single phase	
RATED POWER			
Cooling mode	kBtu/h	77.10	95.50
	kW	22.60	28.00
Heating mode	kBtu/h	85.30	108.50
	kW	25.00	31.50
ELECTRICAL PARAMETERS			
Phase/Voltage/Frequency		1P/220-240V/50-60Hz	
PERFORMANCES			
Airflow (LS/MS/HS)	m ³ /h	2500/3900/4200	3500/4390/5200
Sound power level (LS/MS/HS)	dB(A)	47/51/55	54/58/62
INSTALLATION			
External dimensions (WxHxD)	mm	1330x500x895	
Shipping dimensions (WxHxD)	mm	1590x690x1087	
Net weight/Gross weight	kg	103/146	
Liquid pipe diameter	inches	1/2"	
Suction pipe diameter	inches	7/8"	
External static pressure (standard/max.)	Pa	100/250	

DVFA Ducted high static pressure Fresh Air

VRF
Indoor units



RWV05
included

THE + « USER »

> 100% fresh air inlet.

THE + « INSTALLER »

> Installation compatible to all types of ducting network.

THE + « TECHNOLOGY »

> Adaptability to the ventilation network thanks to its adjustable static pressure.

+ PRODUCT

- RWV05 remote control included (see page 61)
- Fresh air inlet
- Adjustable static pressure from 20 to 200 Pa



RCV03
(optional)



RWV03
(optional)

TECHNICAL DATA

INDOOR UNIT		DVFA-140N-01M22	DVFA-280/220N-01M22	
Part number		7VF030002	7VF030001	
Phase		Single phase	Single phase	
RATED POWER				
Capacity	HP	6.00	9.00	12.00
Cooling mode	kBtu/h	47.70	77.10	95.50
	kW	14.00	22.60	28.00
Heating mode	kBtu/h	30.40	51.80	60.80
	kW	8.90	15.20	17.80
ELECTRICAL PARAMETERS				
Phase/Voltage/Frequency		1P/220-240V/50-60Hz		
PERFORMANCES				
Airflow (LS/MS/HS)	m ³ /h	1070/1460/2600	1320/1900/2300	1820/2400/2800
Sound pressure (LS/MS/HS)	dB(A)	42/47/48	50/52/55	52/54/55
Sound power level (LS/MS/HS)	dB(A)	56/60/61	60/65/68	62/66/68
External static pressure (standard/max.)	Pa	100/185	100/200	
Air return dimensions	mm	1100x255	1510x255	
Air supply dimensions	mm	852x255	1510x255	
INSTALLATION				
External dimensions (WxHxD)	mm	1355x360x876	1725x360x876	
Shipping dimensions (WxHxD)	mm	1386x418x966	1830x530x990	
Net weight/Gross weight	kg	61/77	120/140	
Liquid pipe diameter	inches	3/8"	3/8"	
Suction pipe diameter	inches	5/8"	1"	

FEATURES

TECHNOLOGY



ELECTRONIC EXPANSION VALVE

AIR QUALITY / CLEAN



FRESH AIR

FUNCTIONS USERS



I FEEL



24 H

PROGRAMMABLE
TIMER



RESTART

AUTO RESTART
(MEMORY)



VRF Indoor units


XVVA Console



RCV03
included

+ PRODUCT

- RCV03 remote control included (see page 60)
- DC Inverter centrifugal fan
- Compact unit
- Bidirectional airflow
- Dry contact available



RWW05
(optional, see
configuration
page 61)

FEATURES

TECHNOLOGY



ELECTRONIC
EXPANSION VALVE

FUNCTIONS USERS



I FEEL



SUPER
QUIET



PROGRAMMABLE
TIMER



AUTO RESTART
(MEMORY)

INSTALLER FUNCTIONS



DRY CONTACT
ON/OFF

THE + « SUSTAINABLE DEVELOPMENT »

- > Energy savings (mode locking, setpoint limits).

THE + « USER »

- > New simple and elegant design.
- > Super-quiet unit.
- > Upward and downward blowing for greater comfort.
- > Multiple applications can be connected using the dry contact: room card, presence detector.

THE + « INSTALLER »

- > Very compact.
- > Ideal solution for rooms with low ceilings.

THE + « TECHNOLOGY »

- > Optimal regulation thanks to its electronic expansion valve.

TECHNICAL DATA

INDOOR UNIT	XVVA-050/035/025N-01M22			
Part number	7VF070001			
Phase	Single phase			
RATED POWER				
Cooling mode	kBtu/h	9.50	12.30	17.00
	kW	2.80	3.60	5.00
Heating mode	kBtu/h	10.90	13.60	18.50
	kW	3.20	4.00	5.50
ELECTRICAL PARAMETERS				
Phase/Voltage/Frequency	1P/220-230V/50-60Hz			
PERFORMANCES				
Airflow (VLS/LS/MS/HS/VH)	m ³ /h	270/310/390/460/540	270/350/420/500/580	270/390/460/540/620
Sound pressure (VLS/LS/MS/HS/VH)	dB(A)	30/33/38/42/45	30/36/40/44/47	30/38/42/45/48
Sound power level (VLS/LS/MS/HS/VH)	dB(A)	45/48/52/55/58	47/51/54/57/60	42/48/55/58/61
INSTALLATION				
External dimensions (WxHxD)	mm	600x700x210		
Shipping dimensions (WxHxD)	mm	695x783x303		
Net weight/Gross weight	kg	15.2/18.7		
Liquid pipe diameter	inches	1/4"		
Suction pipe diameter	inches	1/2"		

Table with 2 columns and 40 rows, all cells are empty.

VRF connection with an air handling unit

+ PRODUCT

- Allows the combination of air handling units (AHUs) with the VRF system.
- Compatible with VVFA and VVTA systems (from 4 to 104 HP).
- Five sizes available from 3.5 to 73 kW (1-26 HP).
- The kit includes the regulation part and the EEV part (the regulation part can be remote up to 5 m).
- Possibility of regulation by 0-10V signal from the DDC controller (supplied by the installer).
- Connect up to 4 AHU kits per DRV system for higher battery capacity or to power 4 different AHUs.
- Status outputs available for defrost, alarm, mode, On/Off and compressor status.
- Air handling unit fan control possible from the kit (On/Off and 3 speeds) via 230V outputs to be relayed.



Building



Shopping center



Hospital

AHU CONNECTION KIT

Airwell offers a range of connection kits, to connect VRF outdoor units to an air handling units, alone or with indoor units.


SYSTEM APPLICATION

- ▶ Offer a solution for large spaces by combining the advantages of VRF with those of central air handling units.
- ▶ **Meet the standards of European law:** The minimum fresh air renewal is 25 m³/h of air per person. So this means that every office, every store and the majority of commercial buildings must be equipped with an AHU to meet the standard. With our AHU kit solution you will meet this requirement and at the same time guarantee a high energy efficiency for heating and cooling production.

4 CONTROL MODES AVAILABLE

CONTROL MODE A


- > DDC 0-10V signal output.
- > The AHU kit receives a 0-10V signal to adjust the capacity of the ODU.



Note: The wired remote control is optional. If the DDC can provide the 0-10V signal, on/off, mode and fan speed via dry contacts to the AHU kit, it is not necessary to connect the wired remote control. Otherwise, the wired remote control is required.

CONTROL MODE B


- > Control temperature via DDC.
- > DDC 0-10V signal output.
- > The AHU kit receives a 0-10V signal to adjust the setpoint temperature.



Note: The wired remote control is optional. If the DDC can provide the 0-10V signal, on/off, mode and fan speed via dry contacts to the AHU kit, it is not necessary to connect the wired remote control. Otherwise, the wired remote control is required.


CONTROL MODE C (special application)

- > Without DDC.
- > The wired controller is necessary for the selection of the mode and the speed of ventilation but not necessary for the regulation.
- > The third-party thermostat provides the On/Off signal to the AHU kit when the set temperature is reached.
- > Applicable for some cases with constant cooling or heating demand and low comfort requirements.



CONTROL MODE D

- > Similar to the original AHU V1.0 kit.
- > Control AHU as VRF indoor units with the wired remote control.
- > Return/room temperature control.
- > Wired controller is required.
- > Control method for combination of VRF indoor units and AHU system.



AHU KITS

MODEL	DESIGNATION	PART NUMBER
AHU kit 7	• AHU kit <7 kW	7ACELH033
AHU kit 14	• AHU kit 7 kW to 14 kW	7ACELH034
AHU kit 28	• AHU kit 14 kW to 28 kW	7ACELH035
AHU kit 56	• AHU kit 28 kW to 56 kW	7ACELH036
AHU kit 73	• AHU kit 56 kW to 73 kW	7ACELH037



CONTROL SYSTEMS

Range

MODEL

p.56 COMPATIBILITY TABLES

p.57 FUNCTION TABLES

p.58



ADV05
Central control solutions

p.58



RWV06
Central remote control

p.59



RWV09
Control unit with wifi option

p.60



RCV03
Infrared remote control

p.61



RWV05
Wire controller

VOIR AUSSI

p.6







AIRCONNECT SMART APP

p.8



AIRCONNECT PRO APP

VRF


MODEL	WIRED REMOTE CONTROL			
REFERENCE	RWV03	RWV05	RWV06	RWV09
Part number	7ACELH032	7ACELH039	7ACELH023	7ACELH038
Picture				
HVVA	●	●	●	●
CVQA	●	●	●	●
CVTA	●	●	●	●
fvva	●	●	●	●
DVLA	●	●	●	●
DVMA	●	●	●	●
DVHA	●	●	●	●
XVVA		●	●	●


● Standard remote

● Optional remote

FUNCTION TABLES

VRF

MODEL	WIRED REMOTE CONTROL			
REFERENCE	RWV03	RWV05	RWV06	RWV09
Part number	7ACELH032	7ACELH039	7ACELH023	7ACELH038
Picture				
USUER FUNCTIONS				
On/Off timer	●	●	●	●
Weekly timer			●	●
Silent mode/low speed fan	●	●	●	●
"I Feel" function		●		
Clean-up function	●	●		
Night mode (economy mode)		●		
Remote locking		●	●	●
Turbo mode				
"Follow me" function (presence detector)				
Low battery	●	●	●	●
WiFi compatibility				●
INSTALLER FUNCTIONS				
Technician test mode				
Group control	●	●	●	●
Centralized control			●	●
Heating mode only		●	●	●
Operating fault display	●	●	●	●

*Only one gateway:***CENTRAL CONTROL OR MODBUS**

REMINDER:
ADV05 gateway
not necessary
with the VVTA and
VVEA ranges

TOUCH SCREEN CENTRAL REMOTE CONTROL RWV06 (up to 256 indoor units)



This command allows you to control and monitor the status of indoor units:

- > Modern design.
- > Intuitive and simple operation thanks to its 7" touch screen.
- > Controls until 64 indoor systems by system and 256 indoor units by central control.
- > Can monitors until 32 systems.

The main functions are:

- > Reading operating parameters.
- > Visualization of error codes.
- > Weekly time: mode, fan speed, temperature.
- > Sets LIFO (last enter have high priority).
- > Creation and monitoring zones.
- > ModBus RS485 -+.

PART NUMBER: 7ACELH023

CONTROL UNIT **RWV09** (up to 64 indoor units)






This command allows you to check the status of the indoor units and control them remotely!

- > WiFi included in the control unit.
- > Natively compatible with the AirConnect Smart app.
- > Clean and modern design.
- > 5 inches TFT LCD touchscreen with backlight.
- > Control up to 64 indoor units per system and per control unit.
- > The controller can be connected directly to VVTA and VVEA systems.
- > Possibility to connect up to 32 systems. Eco, Cool only / Heat only can be configured according to actual needs.

Main features:

- > Reading and operating parameters.
- > History and display of error codes.
- > The weekly timer for some or all of the units can be set only once, except for the date or the duty cycle. Editing indoor unit information.
- > Modbus RTU signal output: can be combined with a WiFi module or a third-party device.



PART NUMBER: 7ACELH038

- Current number of indoor units. By default, all existing indoor units are displayed, you can drag them up or down to view them. You can click on the second icon below to select the indoor units you want to view.
- Time.** You can set the time through "HOME-SETTING-TIME".
- Click to return to the home page.
- Click to select the indoor units you want to view.
- Icon display interface.
- List display interface.
- Click to display the checklist.
- AC-1.2: represents the gateway addressed as NO.1, and its central address is NO.2.
- If there is an error in progress, the icon is displayed.
- Set temperature.
- Current room temperature.
- THE CURRENT MODE IS "COOLING".
- Current fan speed is "AUTO".
- Current control mode is "LAST IN FIRST OUT". (last in, first out).

RCV03

Infrared remote control

FUNCTIONS




MODEL		RCV03
Part number		7ACELH045
On/Off		•
Mode	• Auto	•
	• Cooling	•
	• Heating	•
	• Dehumidification	•
	• Ventilation	•
Temperature adjustment		•
Ventilation adjustment		•
Quiet		•
Turbo		•
Health		•
Night mode		•
Timer		•
Airflow	• Horizontal swing	•
	• Vertical swing	•
Electric heating		•
Menu	• Self-cleaning	•
	• Fresh air	•
	• Health airflow	•
	• IFP	•
Menu	• Individual shutter control for CFV cassettes	•
	• Frost protection mode	•
	• C°/F°	•
Locking		•
Switch off/on the display		•
Back lighting		•

RWV05


Wire controller

FUNCTIONS

MODEL		RWV05
Part number		7ACELH039
Fonction de base	• On/off	•
	• Adjusting the setpoint temperature	•
	• Fan speed selection	•
	• Selecting the operating mode	•
Display	• Airflow adjustment	•
	• Clock	•
	• Temperature display	•
Function	• Humidity level display	•
	• Individual control: one control per indoor unit	•
	• Group control: one command to control up to 16 indoor units	•
	• On/off timer	•
	• Individual shutter adjustment (for cassette units with 360° rounded corners)	•
Installation	• Infrared signal receiver: allows the joint use of an infrared control for ducted units	•
	• Display of error codes	•
	• Static pressure adjustment for ducted units	•



ACCESSORY	PHOTO	PART NUMBER	MODEL	FUNCTION	FOR WHAT UNITS?	OPTION/COMMENT
INFRARED CONTROLLER RECEIVER						
INFRARED CONTROLLER RECEIVER		7ACELH009	REC01	<ul style="list-style-type: none"> Realize infrared control. 	<ul style="list-style-type: none"> Ducted 	
BMS SOLUTIONS & MAINTENANCE						
CENTRAL CONTROLLER GATEWAY AND MODBUS/RTU		7ACELH027	ADV05	<ul style="list-style-type: none"> RWV06 and RWV09 adaptor and ModBus/RTU gateway. 	<ul style="list-style-type: none"> VVFA 	<ul style="list-style-type: none"> See configuration page 61
MAINTENANCE TOOL		7ACELH014	TD02	<ul style="list-style-type: none"> Working parameters monitoring and recording tool. 	<ul style="list-style-type: none"> VVFA VVTA VVEA 	

ACCESSORY	REFERENCE	PICTURE	PART NUMBER	FUNCTION
COPPER				
INSULATED COPPER M1	1/4"-3/8" - 10ml		7ACFH0810	<ul style="list-style-type: none"> Refrigerant tubing to connect outdoor unit with indoor unit (monosplit and multisplit).
	1/4"-1/2" - 10ml		7ACFH0811	
	3/8"-5/8" - 10ml		7ACFH0812	
	1/4"-3/8" - 7ml		7ACFH0813	
	1/4"-1/2" - 7ml		7ACFH0814	
	3/8"-5/8" - 7ml		7ACFH0815	
OUTDOOR UNIT BRACKETS				
WALL BRACKET	Max. load 160 kg Horiz. 560 mm Vert. 365 mm Barre 800 mm		7ACTL0506	<ul style="list-style-type: none"> Bracket for outdoor unit installation (monosplit and multisplit).
ANTI-CORROSION WALL BRACKET	Max. load 160 kg Horiz. 460 mm Vert. 410 mm Barre 790 mm		7ACTL0507	<ul style="list-style-type: none"> Bracket for outdoor unit installation (monosplit and multisplit).
4 ANTI-VIBRATION PADS (KIT)			7ACTL0508	<ul style="list-style-type: none"> Ideal for limiting noise and vibrations (good neighborhood).
FLOOR MOUNT RECYCLED RUBBER (PAIR)	Length 600 mm		7ACTL0509	<ul style="list-style-type: none"> Necessary for a professional installation. High quality: using rubber.
	Length 1000 mm		7ACTL0510	
FLOOR MOUNT (PAIR)	450x100 mm		7ACTL0513	<ul style="list-style-type: none"> Necessary for a professional installation. Good quality price ratio: using PVC.

ACCESSORY	REFERENCE	PICTURE	PART NUMBER	FUNCTION
VRF FRAME				
VRF FRAME 4 FEET	Max. charge 500 kg 1000x1200 mm		7ACTL0514	• Available for all VRF outdoor unit range.
VRF FRAME 6 FEET	Max. charge 1040 kg 2000x1200 mm		7ACTL0515	• Available for all VRF outdoor unit range.
VRF EXTENSION 2 FEET	Max. charge 500 kg 1000x1200 mm		7ACTL0516	• Available for all VRF outdoor unit range.
CONDENSATE PUMP				
CONDENSATE PUMP MINI FLOWATCH MF2			7ACTL0517	• Evacuates condensates from indoor units.
CONDENSATE PUMP FLOWATCHDESIGN			7ACTL0518	• Evacuates condensates from indoor units.



Regulations ON R410A FLUID CONCENTRATION

CALCULATION EXAMPLE

Classic case of a hotel, i.e. a category "A" building.

THE PROJECT/EXAMPLE CHARACTERISTICS ARE:

- ▶ Typical 2-3* hotel.
- ▶ DRV system designed to supply 12 to 16 rooms.
- ▶ Outdoor unit model 280 (10 HP).
- ▶ Reversible VRF that can supply up to 16 units.
- ▶ 11 kg of R410A refrigerant recommended.
- ▶ Smaller bedroom, bathroom included:
13 m² > volume = 32.50 m³.
- ▶ CMV ventilation of 60 m³/h, i.e. 10 m³ in 10 minutes.

THIS GIVES THE FOLLOWING CALCULATION:

- ▶ Room volume to take into account:
32.50 + 10 = 42.50 m³.
- ▶ **MAXIMUM LOAD UNDER THE STANDARD:**
0.44 kg/m³ x 42.5 m³ = 18.7 kg of refrigerant
- ▶ Since the calculation is determined for the room with the smallest volume, the total refrigerant capacity of the installation must be taken into account:
 - Outdoor unit (11 kg) + network backup.
 - The network back-up is calculated according to the lengths and diameters of the copper piping used. See refrigeration diagram.
- ▶ **MAXIMUM PROJECT LOAD CALCULATION:**
11 kg + (4.520 kg) = 15.520 kg of refrigerant

COMPLIANT WITH REGULATIONS

MEASURE UNITS

Conversion

LENGTH			
1 inch (in)	0.0254 m		
1 foot (ft)	12 inches	0.3048 m	
1 yard (yd)	3 feet	0.9143 m	
1 mile (mi)	1.760 yards	1609 m	
1 nautical mile (nmi)	1852 m		
1 meter (m)	39.37 inches	3.28084 feet	1.09361 yard

MM	INCHES
6.35	1/4
9.52	3/8
12.70	1/2
15.88	5/8
19.05	3/4
22.22	7/8
25.40	1
28.58	1 1/8
31.75	1 1/4
38.10	1 1/2

VOLUME	
1 cubic inch (cu in)	16.387064 cm ³
1 cubic foot (cu ft)	0.028317 m ³ /28.31685 dm ³
1 cubic yard (cu yd)	0.76455 m ³
1 pint	0.568 l
1 gallon-imp	4.546 l
1 gallon (US gal)	3.78541 l or dm ³
1 cubic meter (m ³)	35.31467 cu ft
1 cubic decimeter (dm ³)	0.26428 gal
1 liter (l)	1 dm ³

HP (HORSE POWER) *	BTU	KW
1	9000	2.637
1.5	12000	3.516
2	18000	5.274
2.5	24000	7.032
3	30000	8.79
5	45000	13.185

MASS VOLUME	
1 cu.ft/lb	62.43 dm ³ /kg
1 US gallon/pound	8.3 dm ³ /kg

DENSITY	
1 pound/cu.ft	0.016 kg/dm ³

MASS		
1 ounce (oz)	28.349 g	
1 pound (lb)	16 oz	0.4536 kg
1 quintal U.S	100 lbs	
1 centweight	112 lbs	
1 short ton (US)	2000 lbs	907.18 kg
1 long ton (GB)	2240 lbs	1016.04 kg
1 quintal (q)	100 kg	
1 tonne (t)	1000 kg	

AREA		
1 square inch (in2)	6.4516 cm ²	
1 square foot (ft2)	0.0929 m ²	
1 square yard (yd2)	0.8361 m ²	
1 square meter (m ²)	1550 in ²	10.76391 ft ²

ENERGY - HEAT QUANTITY		
1 cal	4.18 joules	
1 Btu	0.252 kcal	1055 joules
1 Btu/lb.°F	1 kcal/kg °C	
1 kcal	1 millithermie	
1 fg/h	-1 kcal/h	
1 kcal/h	1.163 W	
1 Btu/h	0.293 W	
1 ton (US)	3024 kcal/h	3512 W
1 ton (GB)	3340 kcal/h	3878 W
1 watt (thermic)	0.86 kcal/h	

° Fahrenheit = °C x 9/5 + 32 / ° Celsius = (°F-32) x 5/9 / ° Celsius = T (Kelvin) - 273.15.
 * Indicative values

Rated capacities of our products are given for air conditions as following:
 Cooling mode: 35°C out/27°C in (Dry bulb)
 Heating mode: +7°C out/20°C in (Dry bulb)

NEW PRODUCT *naming system*

Discover below some tips to decipher our references and product codes more quickly.

1 ► UNDERSTANDING PRODUCT CODES


DIGIT N° 1	DIGIT N° 2 & 3 Product constitution	DIGIT N° 4 & 5 subfamily
2	AirSolar	VF VRF
7	Airwell	OG Chilled water terminal
E	Electra	KT Kit
J	Johnson	MB Monoblock
		SP Split (2 units)
		CK Unassembled product
		PR Spare part
		EN Renewable energy
		01 Floor ceiling
		02 High wall
		03 Ducted
		04 Cassette
		05 Window
		06 Monosplit condensing unit
		07 Console
		08 Portable
		09 Multisplit condensing unit
		10 Floor standing
		11 Airflow
		12 Rooftop unit
		13 Hydraulic module
		17 Thermodynamic water heater
		18 Vertical cabinet
		14 Monoblock condensing unit
		15 VRF water source
		19 Water source
		20 Water condenser
		21 Water-cooled condensing unit
		22 Hybrid panel
		23 Photovoltaic panel
		24 Heating panel
		25 Micro-inverter

2 ► UNDERSTANDING ACCESSORY CODES

DIGIT N° 1	DIGIT N° 2 & 3	DIGIT N° 4 & 5 (& 6)
7	Airwell assembled product	AC Accessories
		EL Electricity kit - Heating
		ELH Electricity kit - Heating / VRF
		FH Cold & hydraulic kit
		FHH Cold & hydraulic kit / VRF
		TL Sheeting Kit / Casing & Metal sheet Kit
		VF Fan & airflow kit
		VFH Fan & airflow / VRF kit

3 ► UNDERSTANDING SERIAL NUMBERS

Each unit (IDU or ODU) is also identify with a unique serial number which can assist tracing the unit.



ARTICLE 1 - PURPOSE AND SCOPE

1.1. These general terms and conditions of sale apply to all sales of equipment and deliveries of services entered into by Groupe Airwell SA (hereinafter the "Vendor"), a public limited company (société anonyme) with a capital of 217 361 euros whose registered office is located at 10, rue du Fort de Saint Cyr, 78180 Montigny le Bretonneux, France, entered in the Versailles trade and companies register under number 752 800 862 from a professional buyer, understood as any natural or legal person, public or private, who acts for purposes within the framework of his commercial, industrial, craft, liberal or agricultural activity, including when they act in the name and on behalf of another professional. These general terms and conditions of sale are not applicable to a consumer or non-professional buyer.

1.2. "Equipment" refers to finished products, accessories, and spare parts.

1.3. Any order implies full and unconditional acceptance of these general terms and conditions of sale, which prevail over any other document of the buyer, particularly its general terms and conditions of purchase, unless otherwise expressly agreed beforehand by the Vendor.

1.4. If the Vendor does not invoke any clause within the general terms and conditions of sale at a given moment, this may not be interpreted as waiving its rights to invoke such clauses or these general terms and conditions of sale subsequently.

ARTICLE 2 - GENERAL INFORMATION: CATALOGUES, DOCUMENTATION

2.1. Due to the speed of technological developments and changes to standards or safety improvements in the sector concerned, any information, indication, or item of value transmitted on any medium, whether it comes from the manufacturer or the Vendor, is given for information purposes only. These parties reserve the right to make any modification to the equipment whose prints, photographs, or drawings appear in such documents, at any time and without notice. No document provided by the Vendor is to be considered as a contractual element, and the Vendor cannot be held liable for such documents.

2.2. Where the proposed equipment is selected by the Vendor on the basis of information provided by the informed professional buyer, the buyer is always responsible for ensuring that the characteristics of the equipment proposed by the Vendor are actually suitable for its needs, with regard to both performance and the possibilities of implementation. In addition, if the buyer resorts to hiring the Vendor's engineers or technicians for a study or project, the Vendor may not be held responsible, and the buyer undertakes to consult an expert in the field for, among other things, the selection and sizing of the equipment, as well as its installation and commissioning.

2.3. The buyer must not modify the markings affixed on the equipment or packaging, add any other marking, or use the Vendor's markings, names, or trademarks in any way not expressly authorized.

ARTICLE 3 - ORDERS AND QUOTATIONS

3.1. Orders are fixed. Once accepted, the order or quotation may only be modified or cancelled by the buyer with the Vendor's prior express consent. The buyer shall be liable for any order cancellation, even partial, and the Vendor shall be entitled to compensation in the form of a penalty set in the amount of the cancelled order, without prejudice to any other damages.

3.2. Any acceptance of an order or quotation must be written. Sales are final only after the express acceptance in the form of the Vendor issuing an acknowledgement of receipt of the buyer's order. The Vendor reserves the right to accept or reject any order within a maximum of five business days from its receipt.

3.3. The buyer must check the acknowledgement of receipt of the order, and report any error or omission to the Vendor within a maximum period of 48 hours from its receipt. Beyond this period, the order becomes final for the buyer. If a buyer places an order with the Vendor, without having paid for its previous order(s), the Vendor may refuse to fulfil the order and deliver the equipment in question, without the buyer being able to claim any compensation for any reason whatsoever.

3.4. The Vendor reserves the right, even after partial fulfilment of an order, to require guarantees or to cancel the order(s) or balance of orders in progress in the name of the buyer, without any kind of compensation, in the following cases: deterioration of the buyer's credit, failure to file documents and instruments with the registry of the commercial court, downgrading of the buyer's rating by the Vendor's credit department, refusal of a credit insurer or a factor to cover the amount of the sale, change or modification in the financial or legal capacity of the buyer, listings or liens on the buyer's business or in general, in case of a change in the buyer's situation.

ARTICLE 4 - DELIVERY AND TRANSPORT

4.1. Unless there are provisions or an agreement to the contrary, the transport/delivery costs are borne by the purchaser. The reference incoterms are FCA purchaser's warehouse or FOB port of shipment from the manufacturing plants.

4.2. The delivery lead times are given for information purposes only. In no case may exceeding the lead times justify the cancellation of the order or the awarding of damages. However, if the equipment still has not been delivered two months after a formal notice has remained unacted on, for any reason other than force majeure (as defined in article 6.2), the order may then be cancelled at the request of either party; the buyer may obtain a refund of its advance payment to the exclusion of any other compensation or damages.

4.3. In accordance with Article 133-3 of the French commercial code, any delivered equipment that was not the subject of reservations by registered letter with acknowledgement of receipt within three days of receipt (not including holidays) to the transporter, a copy of which shall be simultaneously sent to the Vendor, shall be considered accepted by the buyer.

ARTICLE 5 - RECEIPT AND RETURN OF EQUIPMENT

5.1. Complaints about apparent defects or the non-compliance of the delivered equipment must be expressed in detail on the delivery slip and by registered letter with acknowledgement of receipt, and sent to the Vendor's registered office within 72 hours after delivery. Beyond this period, the received equipment shall be considered compliant with the order. It shall be up to the buyer to provide, with its complaint, any justification as to the reality of the defects or anomalies observed. The buyer shall give the Vendor every opportunity to investigate such defects and find a solution.

5.2. In any case, the buyer may not return the equipment without authorization from the Vendor. The Vendor shall be responsible for the costs and risks of the return solely in the event that an apparent defect or missing items are actually noted by it or its representative. If a claim proves justified, the return shall be the subject of an exchange or a credit memo, at the Vendor's choice, without the ability to demand any compensation or damages in any capacity whatsoever. Any return of equipment previously accepted due to the buyer, including but not limited to an order error or incorrect information communicated for a calculation or an order made by the buyer, shall automatically result in a discount of 20% from the amount of the equipment in question excluding taxes, in order to take account of the costs of repackaging and any other charges, including transport, generated by this return. The buyer shall be responsible for the return transport.

ARTICLE 6 - PRICE - PRICELIST AND PRICE REDUCTIONS

6.1. Unless there are provisions or an agreement to the contrary, prices are set in euros excl. tax and FCA purchaser's warehouse for sales from the seller's stock, or FOB port of shipment from the manufacturing plants. For sales from manufacturing plants, a handling/freight/loading fee of 470 euros per container (regardless of container type) will be charged.

6.2. Equipment is sold based on the Vendor's pricelist still valid on the date of each placed order, or on the date of issue of each quote, subject to delivery occurring no later than the end of the second calendar month following that date. Beyond that period, any price change before delivery shall be automatically applicable.

6.3. No discount shall be applied by the Vendor for cash payment or for payment earlier than the period indicated in these general terms and conditions of sale, or on the invoice issued by the Vendor.

6.4. Unless otherwise agreed, the Vendor may grant the buyer discounts on the valid pricelist, including in the form of premiums, at the time when the order is placed, depending on the turnover excluding taxes generated annually or over a given period, and/or the quantity/nature of the purchased finished products and/or services possibly rendered by the buyer. These discounts may be fixed and/or gradual and may vary according to the buyer category.

6.5. If one of the criteria for application of these price reductions or any one of the clauses of these terms and conditions of sale is not met, the cancellation of such price reductions shall be immediately retroactive over the entire year in question. Consequently, if price reductions have already been applied by the Vendor during the year in question, they must be returned by the buyer on simple request.

ARTICLE 7 - PAYMENT TERMS

7.1. For any company based outside France, invoices shall be payable according to the payment period negotiated and agreed by the Vendor. For all French companies, invoices are payable within a maximum period of 45 days, end of month, or 60 days from the invoice issue date. For summarized invoices issued at the end of the month, the period must not exceed 45 days from the invoice issue date (article L. 441-6 of the Code of Commerce).

7.2. The Vendor reserves the right to require one or more advance payments when the order is placed and/or before shipment. Any commercial paper (bill of exchange or promissory note) presented for acceptance must be returned within eight clear days of its receipt by the buyer.

7.3. In accordance with Articles L. 441-3, L. 441-6, and D. 441-5 of the French commercial code, any payment delay automatically results in, in addition to late payment penalties at a rate equal to three times the statutory interest rate (i.e., 3.12% in the first half of 2022 updated each half-year period by the Minister of the Economy, with the understanding that this rate shall apply to the amount of the invoice including all taxes), an obligation for the debtor to pay 40 euros in recovery charges if the invoice has not been settled on the day following the payment date appearing on the invoice. In addition, in case of a late payment or a partial payment, (i) the Vendor may suspend all current and/or future orders; (ii) 48 hours after a formal notice has remained unacted on, the sale shall be automatically terminated, if so desired by the Vendor, which may move for summary proceedings for the return of the equipment, without prejudice to any other action and/or damages. The buyer must reimburse all costs caused by the non-payment (including return costs on unpaid debts) and the recovery of sums due, including fees of ministerial officers and/or recovery companies.

7.4. By no means may payments be suspended or offset without the Vendor's prior written approval. Any partial payment shall first be applied to the non-preferential part of the debt, then on the amounts with the earliest due date.

ARTICLE 8 - RETENTION OF TITLE AND TRANSFER OF RISKS

8.1. The transfer of ownership of the equipment is subject to the full payment of the price by the buyer. The buyer undertakes to maintain the equipment in good condition and insure it against all risks, for which the buyer shall be fully liable in all cases, as from their delivery. In order to permit any action for recovery by the Vendor, the buyer must ensure that the equipment can be individually identified.

8.2. The Vendor may recover its equipment regardless of whose possession it is in, in case of non-payment of the price by the buyer or insolvency thereof, even when such equipment has been handed over to a third party. If the equipment was resold, the buyer must notify the new buyer of the existence of the retention of title clause.

ARTICLE 9 - LOCAL STANDARDS AND COMPLIANCE

9.1. As concerns European countries subject to the FGAS EU517/2014 regulation, the importer of the products bears sole liability to the European authorities for the declaration of the FGAS quotas. Therefore, for orders from Airwell's central stock located in France, the FGAS quotas are declared by Airwell; no further action is to be taken by Airwell customers. For drop-shipped orders, imported directly from plants outside of Europe, the Airwell customer importing this order bears sole liability for the declaration of the FGAS quotas to the relevant authorities. The latter must complete the declaration paperwork in its own country. Airwell may, at the customer's request, sell and transfer FGAS quotas but Airwell shall not be held liable under any circumstances for a failure to declare quotas or any error in the quantities declared. The importing customer bears sole liability for the declaration of FGAS quotas.

9.2. Any entry of goods into the European Union or a third country is the sole responsibility of the importer. In this sense, the buyer is solely responsible for ensuring the conformity of the products it imports. Airwell cannot be held responsible if the products do not comply with the local standards when they enter the "destination" territory (release for consumption). The buyer must provide in advance all the documents necessary for the compliance of the imported products in the "destination" territory (release for consumption). Airwell strongly recommends a pre-departure inspection of the goods, at the customer's (buyer's) expense, to ensure the compliance of the imported goods. After research and analysis, Airwell reserves the right to refuse the order or to modify the pricing.

ARTICLE 10 - ASSIGNMENT OF JURISDICTION - APPLICABLE LAW

These general terms and conditions of sale are subject to French law. Any dispute shall be under the exclusive jurisdiction of the VERSAILLES COMMERCIAL COURT, even in case of interim proceedings, incidental claims, or multiple defendants or introduction of third parties.

ARTICLE 11 - INTELLECTUAL PROPERTY

11.1. The buyer is authorized, on a precarious basis, to use the brand, the commercial name, the sign, the graphic elements and other distinctive signs relating to the Vendor's equipment for the sole purpose of identifying and promoting them and in the exclusive interest of the Vendor. This right of use does not confer any ownership rights to the buyer. The buyer undertakes not to register and not to be the owner of trademarks, models, domain names, patents, signs, trade names, product references and other distinctive signs belonging to the Vendor (or of which it has the use) or which could lead to confusion with its own.

11.2. With regard to the Vendor's graphic elements, such as logos or photographs, the buyer undertakes to use and reproduce them only in strict compliance with the quality of the image and the format of the original graphic elements. The buyer shall not modify them or use them in such a way as to degrade the brand image of the Vendor or those image of the Vendor or of his equipment.

11.3. The buyer's right to use the Vendor's trademarks, trade names or other distinctive signs shall cease immediately when the business relationship with the Vendor ceases for any reason whatsoever. Same applies to non-compliance by the buyer with the conditions of use described in this article may result in the termination of this right of use at any time by simple letter.

ARTICLE 12 - PRIVACY POLICY

12.1. Any order for equipment implies the processing, by the Vendor, of personal data within the meaning of European Regulation 2016/679 of 27 April 2016 and Law No. 78-17 of 6 January 1978 relating to data processing, files and freedoms in its current version (hereinafter collectively the "Applicable Laws"), which relate to the buyer and/or the natural person, representative of the buyer, who places the order in the name and on behalf of the buyer.

12.2. The Vendor declares that it complies with the Applicable Laws and, in particular, implements the principles of personal data protection, notably the principles of lawfulness, proportionality, transparency and data minimization as set forth in the Applicable Laws.

12.3. The manner in which such data is collected and processed by the Vendor, as well as a description of the buyer's rights with respect to such data, are set out in the privacy policy adopted by the Vendor and available on its website at the URL <https://www.airwell.com/en/privacy-policy/>.

12.4. The Vendor's privacy policy is an integral part of these terms and conditions of sale.

THESE GENERAL TERMS AND CONDITIONS MAY BE SENT TO YOU IMMEDIATELY IN LARGE PRINT ON SIMPLE REQUEST. AS THESE TERMS AND CONDITIONS ARE ESSENTIAL TO THE VENDOR'S COMMITMENT, WE INVITE YOU TO CONTACT US IF THEIR READABILITY IS NOT SUITABLE FOR YOU.



TECHNOLOGY



FLEXY MATCH
Indoor units are compatible with monosplit or multisplit installation.



DC INVERTER
Compressor with high efficiency DC engine.



R410A FLUID
Refrigerant R410A.



ELECTRONIC EXPANSION VALVE
Precise control of refrigerant flow, optimized performance and compressor protection.



4D AIRFLOW
Optimized heating and cooling operations, with an automatic horizontal and vertical swing.



MULTIFLOW 360°
4-direction air distribution system with great comfort through 360°, with motorized opening control.



BLUE FIN TRAITEMENT
Protection of exchangers against corrosion while improving heat transfer.

AIR QUALITY/CLEAN



FRESH AIR
Cools the room by bringing fresh air from outside.

USER FUNCTIONS



I FEEL

Precise temperature control all around the chosen zone via a remote temperature sensor.



PROGRAMMABLE TIMER

Timer set to switch the unit on and off.



AUTO RESTART (MEMORY)

Automatically restarts the unit in the last used mode when power is restored.

INSTALLER FUNCTIONS



ERROR CODE VIA INDOOR UNIT

Digital display of error codes or temperature settings on the indoor unit.



SELF-DIAGNOSTIC

Unit failure indicated by a blinking led on the unit display.



INTEGRATED CONDENSATES PUMP

Eliminates condensate, for a simple and smooth running.



DRY CONTACT ON/OFF

Connection to a detection accessory (room card, presence detector, window..) to make energy savings.



BMS COMPATIBLE

Connection to the BMS system.



SERVICE MONITOR TOOL

Local interface for monitoring the operating parameters.

AS PART OF ITS INVOLVEMENT IN THE
ENERGY TRANSITION
AIRWELL HAS IMPLEMENTED THE

Airwell ACADEMY

TECHNICAL & QUALIFICATION TRAINING

to allow maintenance technicians, installers and distributors to develop their knowledge and offer them an energy management system that is both essential for their activity but also for the planet!



Read more about training at:
www.airwell-academy.fr

AFTER-SALES
SERVICE

+33 (0)1 76 21 82 95

Monday to Friday 9 am-12:30 pm / 2 pm-5 pm

TECHNICAL SUPPORT

sav@airwell.com

GROUPE AIRWELL

10, rue du fort de Saint Cyr - 78180 Montigny-le-Bretonneux, FRANCE

Tél.: +33 (0)1 76 21 82 00 - www.airwell.com

Printed in France